

# USB Crash Cart Adapter with File Transfer & Video Capture

Product ID: NOTECONS02



The USB crash cart adapter gives you control of a headless system, turning your laptop into a portable crash cart for rack servers, PCs, ATMs, kiosks, and more.

## Instant System Access

Simply connect the laptop crash cart adapter to your computer using the included USB cable, then connect the integrated USB and VGA cables to your server for instant BIOS-level control. With no server-side software required, you can be up and running instantly.



## **Troubleshoot More Efficiently**

With the flexible software interface, you can transfer files from your laptop to the server, capture videos for records or instructional purposes, take screenshots and scale the display window to full screen mode or smaller, with no scroll bars helping you to troubleshoot faster.

## **Self-Powered Reliability**

Powered from the server-side USB connection, the KVM adapter doesn't require an AC outlet so you can connect to any PC or device that has a VGA and USB port, even if there's no power outlet available.

## **Take It Anywhere**

This pocket-sized adapter features a compact design that easily fits inside your laptop bag and requires no additional accessories to connect, eliminating the need to lug around a large, awkward traditional crash cart to troubleshoot and service your systems.

StarTech.com offers a wide selection of high-quality KVM-related products to help you access your systems more efficiently without the expense and clutter of extra keyboards, mice and monitors. This USB KVM crash cart adapter is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- ATM and VLT maintenance and repair
- Mobile systems and server repair

### Features

- Access any VGA and USB system directly from your laptop via the KVM console adapter
- Set up quickly with included cables and instant BIOS-level control
- Share troubleshooting information and display errors with video capture at 1920 x 1200 60Hz
- Simple self-powered portability with no external power adapter necessary
- Easily troubleshoot systems with bi-directional file transfers between local and remote computer

<b>Hardware</b>	Warranty	2 Years
	Audio	No
	Cables Included	Yes
	Daisy-Chain	No
	KVM Ports	1
	Number of Monitors Supported	1
	PC Interface	USB
	PC Video Type	VGA
	Rack-Mountable	No
<b>Performance</b>	Hot-Key Selection	No
	IP Control	No
	Maximum Analog Resolutions	1920x1200 @ 60Hz
	Maximum Number of Users	1
	MTBF	909000
	On-Screen Display	No
<b>Connector(s)</b>	Console Interface(s)	1 - USB Mini-B (5 pin) Female Input
	Host Connectors	1 - USB Type-A (4 pin) USB 2.0 Male
		1 - VGA (15 pin, High Density D-Sub) Male
<b>Software</b>	OS Compatibility	Windows® XP, Vista, 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS® 10.9 to 10.14 Linux 2.6 to 4.11 <i>LTS versions only</i>
<b>Special Notes / Requirements</b>	<b>Note</b>	If you're interfacing with a Linux device, this adapter is only compatible with standard QWERTY keyboards in U.S English configuration
<b>Indicators</b>	LED Indicators	1 - Host/Server Keyboard/Mouse USB Link  1 - Host/Server Video (VGA) Link  1 - User Console/USB Link
<b>Power</b>	Power Source	USB-Powered
<b>Environmental</b>	Humidity	80% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)
<b>Physical Characteristics</b>	Cable Length	416 mm [16.4 in]

		1 x 15in (385mm) USB host cable, 1 x 3in (76mm) VGA host cable, 1 x 6ft (1.8m) USB Console cable
	Color	Black
	Enclosure Type	Plastic
	Product Depth	115 mm [4.5 in]
	Product Height	1.5 cm [0.6 in]
	Product Width	74 mm [2.9 in]
	Weight of Product	170 g [6 oz]
<b>Packaging Information</b>	Package Height	46 mm [1.8 in]
	Package Length	30.3 cm [11.9 in]
	Package Width	16.6 cm [6.5 in]
	Shipping (Package) Weight	363 g [12.8 oz]
<b>What's in the Box</b>	Included in Package	1 - USB Crash Cart Adpater
		1 - USB A to Mini-B Cable
		1 - USB Software Key

Product appearance and specifications are subject to change without notice.