

AXIS C1004-E Network Cabinet Speaker

Audio made smart and easy

AXIS C1004-E is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.

- > [Easy music streaming](#)
- > [Voice announcements](#)
- > [All-in-one speaker system](#)
- > [Quick installation with just one network cable \(PoE\)](#)
- > [Future-proof with openness and integration](#)



AXIS C1004-E Network Cabinet Speaker

Models	AXIS C1004-E Network Cabinet Speaker White AXIS C1004-E Network Cabinet Speaker Black	Event actions	Play audio clip, send SNMP trap, send Auto Speaker Test, status LED File upload via HTTP, network share and email Notification via email, HTTP, HTTPS and TCP
Audio		Built-in installation aids	Test tone verification and identification
Audio streaming	One-way/two-way ^a , mono	General	
Audio compression	G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	Casing	IP45- and NEMA 3R-rated Plastic and metal casing Colors: White NCS S 1002-B; black For repainting instructions and impact on warranty, contact your Axis partner.
Audio input/output	Built-in microphone (can be disabled)	Memory	256 MB RAM, 256 MB Flash
Built-in microphone specification	50 Hz - 16 kHz	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3af Type 1 Class 3 (max 12.95 W)
Speaker		Connectors	RJ45 10BASE-T/100BASE-TX PoE
Enclosure	Two-way bass-reflex type Speaker component: 12 cm (4.72 in) dynamic cone speaker, 2.5 cm (0.98 in) balanced dome tweeter	Storage	Support for microSD/microSDHC/microSDXC card Max. size 64 GB For SD card recommendations see www.axis.com
Max sound pressure level	96 dB	Reliability	Designed for 24/7 operation.
Frequency response	60 Hz - 20 kHz	Operating conditions	-20 °C to 50 °C (4 °F to 122 °F) Humidity 10–85% RH (condensing)
Coverage pattern	130° horizontal by 100° vertical	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Amplifier		Approvals	EMC EN 55022 Class A, EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KN24, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-2, CNS 13438 Environment IEC/EN 60529 IP45, IEC/EN 62262 IK10, NEMA 250 Type 3R, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14
Amplifier description	Built-in 6 W Class D amplifier	Dimensions	H x D x W (with bracket): 290 x 200 x 196 mm (11.4 x 7.9 x 7.7 in)
Network		Weight	3.0 kg (6.61 lb)
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X ^b network access control, Digest authentication, User access log, Centralized Certificate Management	Included accessories	Installation Guide, AVHS authentication key, AXIS Camera Station license key, cable shoe, bracket with screws and washers, AXIS Connector Guard A
Supported protocols	IPv4/v6 ^c , HTTP, HTTPS ^b , SSL/TLS ^b , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, SIP (Cisco, Avaya, Asterisk)	Optional accessories	Safety wire kit For more accessories, see www.axis.com
System integration		Video management software	AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Music streaming	Music playback through AXIS Audio Player. Offline streaming from SD card and online streaming support.	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Voice announcement	Up to 50 pre-recorded voice announcements through AXIS Audio Player. Voice announcement through built-in SIP support for connection to any IP telephone /VoIP system and VAPIX support.	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] , AXIS Video Hosting System (AVHS) with One-click Connection, AXIS Camera Application Platform (ACAP).	<p>a. This product supports two-way audio for sending audio to the speaker and receiving audio from the microphone. The product does not support two-way communication for conversations with speaker operators.</p> <p>b. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p> <p>c. Audio synchronization with IPv4 only.</p>	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	Environmental responsibility: www.axis.com/environmental-responsibility	
Audio synchronization	Built-in audio synchronization ^c for up to 50 speakers with unicast and hundreds of speakers with multicast. No additional speaker management software or hardware required.		
Intelligent audio	Auto Speaker Test (verification via built-in microphone)		
Event triggers	Virtual inputs, AXIS Camera Application Platform (ACAP) Call: DTMF, State changes		