

# Rittal – The System.

Faster – better – everywhere.

## ► Sheet steel door, vertically divided, vented for VX IT – DK 5301.652

Date : Nov 11, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Sheet steel door, vertically divided, vented for VX IT – DK 5301.652

created: 11.11.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	To replace existing doors. The vented surface area is approx. 85% perforated.
<b>Material:</b>	Sheet steel
<b>Surface finish:</b>	Spray-finished
<b>Colour:</b>	Door: RAL 7035 Comfort handle VX, hinges: RAL 9005
<b>Protection category IP to IEC 60 529:</b>	IP 20
<b>Assembly instruction:</b>	For a door opening angle of 180° when baying, a 180° baying hinge is required
<b>Supply includes:</b>	Door, vertically divided, with comfort handle VX for profile half-cylinders with security lock 3524 E, r/h side 3 x 180° hinges, fitted on each half of the door Assembly parts
<b>Note:</b>	Door opening angle for stand-alone siting: max. 240° Door opening angle when baying: max. 160°

## Product features

<b>To fit:</b>	Enclosure type: VX IT Width: < 800 mm Height: < 2000 mm
----------------	---

<b>Packs of:</b>	1 pc(s).
------------------	----------

<b>Copper weight (kg per piece):</b>	0
<b>EAN:</b>	4028177955141
<b>Customs tariff number:</b>	94039010
<b>ETIM 7.0:</b>	EC000747
<b>ETIM 6.0:</b>	EC000747
<b>eCl@ss 8.0/8.1:</b>	27182204
<b>eCl@ss 6.0/6.1:</b>	27182290
<b>Product description:</b>	Sheet steel door, vertically divided, ventilated for VX IT, to replace existing doors. The vented surface area is approx. 85% perforated. For enclosure width < 800 mm, for enclosure height < 2,000 mm