













#### Reliabale office solutions

The 19" ProLite E1980S is an LED-backlit monitor featuring a good response time, high contrast, as well as sRGB and gamma correction functions that allow even the finest colour nuances to be adjusted with precision. Additionally, this monitor comes equipped with integrated speakers.

Available also with height adjustable stand: ProLite B1980S-B1

# 01

#### **DISPLAY CHARACTERISTICS**

Diagonal	19", 48cm
Panel	TN
Native resolution	1280 x 1024 @75Hz (1.3 megapixel)
Aspect ratio	5:4
Panel brightness	250 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	12M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: 170°/160°, right/left: 85°/85°, up/down: 80°/80°
Colour support	16.7mln (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 80kHz
Viewable area W x H	376.32 x 301.05mm, 14.8 x 11.9"
Pixel pitch	0.294mm
Colour	matte, black



## INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 DisplayPort x1
HDCP	yes



OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu, + / Volume, -/ Eco, Signal Select (Auto)
User controls	picture adjust (contrast, brightness, i-Style colour, ACR, Eco, OD, X-Res technology), image setup (blue light reducer, sharpness), colour settings (gamma, 6-axis, colour temp.), audio settings (volume, mute), OSD settings (H. position, V. position, OSD time, language), extra (reset, DDC/CI control, signal select, HDMI range, opening logo, power LED, information)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



#### **MECHANICAL**

Display position adjustments	tilt
Tilt angle	21° up; 4° down
VESA mounting	100 x 100mm
Cable management system	yes



## **ACCESSORIES INCLUDED**

Cables	power, HDMI
Other	quick start guide, safety guide



#### **POWER MANAGEMENT**

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	12W typical, 0.5W stand by, 0.3W off mode



# SUSTAINABILITY

Regulations	CE, TÜV-GS, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	D
REACH SVHC	above 0.1%; Lead
ILACII SVIIC	above v. i /o. Leau



#### **DIMENSIONS / WEIGHT**

Product dimensions W x H x D	411 x 402 x 204.5mm
Box dimensions W x H x D	474 x 427 x 122mm
Weight (without box)	3.1kg
Weight (with box)	4.1kg
EAN code	4948570125418

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.