

Acer B6 series

Acer B276HULCymiidprx

The professional and ergonomic everyday monitor

The Acer B6 business series has been specifically designed for intensive everyday use. During development, special emphasis was placed on sophisticated ergonomic features and performance. Your B6 monitor can be tilted, swivelled and adjusted in height by up to 150 mm.

The high-quality displays of the B6 series offer high display quality, analog and digital interfaces, loudspeakers, as well as extended application possibilities.

69cm (27") 5ms 100M:1 ACM 350nits ZeroFrame WQHD IPS LED DVI 2xHDMI DP MM Audio out Height adj. Pivot EURO EMEA TCO7.0 Darkgrey Acer EcoDisplay



Diagonal size: 68.6 cm (27.0 inches)

• Resolution (native): 614x367.90x66

• Response time: 5 ms

Brightness: 350 cd/m²

• Signal input: 1x DVI, 2x HDMI, 1x DP, Audio In/Out



Acer B276HULCymiidprx

SPECIFICATIONS







68.6 cm (27.0 inches) Diagonal size 597x336 mm Active display area (WxH) Aspect ratio 16:9 Pixel pitch (PPI) 2560x1440 IPS Technology Panel type Response time 5 ms Brightness 350 cd/m² Backlight type LED

Acer CrystalBrite Nein, entspiegeltes Display Viewing angle (h/v) CR>10:1 178/178° Viewing angle (h/v) CR>5:1 178/178° Static contrast ratio 1000:1 100M:1

Dynamic contrast ratio Colors 99% sRGB Colour space Speaker 2 x 2 watts Signal input 1x DVI, 2x HDMI, 1x DP, Audio In/Out

Chassis colour Darkgrey Matt DVI / HDMI:31-90kHz / 56-76Hz, DP / Frequency (H/V)

MiniDP:113-113kHz/50-76Hz Refresh rate (max.) 60Hz

2x (1x HDMI 2.0, 1x HDMI 1.4) HDMI 1x (DP 1.2a)

DisplayPort VGA DVI 1x USB 3.1 Type-C USB Hub Audio

Norms and Standards

Warranty 36 Months Carry In TCO, Windows 10 konform, CE, GS, ISO Certification 9241-307, EnergyStar MTBF 30,000 Std. bei 25°C

Dimensions and weight

614x395.40-545.40x247.20 mm Dimension (Wx Hx D) 614x367.90x66 mm Dimension (WxHxD) 21.7 mm Min. thickness without stand 9,5 kg 69x50.50x20.40 Weight (unpacked) Package Dimensions

Weight (packed) 10,12 kg Weight w/o stand

5,17 kg 40 Pcs (131x110x214 cm) Pallet qty and size $(H \times W \times D)$

Containergröße (20'/40') 320 / 720

On/Off, Auto/Exit, left/right (</>), Menue/ Control panel

Enter, e-Key EN, DE, ES, NL, FR, IT, FI, RU OSD languages

Operating ambient temperature 5°C bis 35°C Operating ambient humidity 10% bis 85% Storage ambient temperature -20°C to 65°C

Kensington Security Slot

Power supply and consumption

Power supply Electrical voltage Internal 100/120 V AC; 220/240 V AC; 50/60 Hz Energy Efficiency Class

On-mode Power 32 kWh/1000h Standby mode Power 0,5 W Off mode Power 0,3 W Annual Energy Consumption 58 kWh/Jahr

Tilt angle -5°~35° +/-60° Swivel angle Height adjust range 150 mm +/-90° Pivot function 100x100 mm VESA wall mounting

Model B276HULCymiidprx Produktlinie **B6** Series Part number UM.HB6EE.C10 EAN 4713392581144 Package content

EU- und UK-Stromkabel (1,8m), DVI und Display Port Kabel (1,5m), Audio-Kabel (1,5m),

Quick Start Guide

Special features Acer Display Widget

Due to our ongoing commitment to the continuous improvement of the quality of our products, this data sheet is subject to change without notice. Availability may vary from region to region. Acer is not responsible for any errors or omissions in the product descriptions. Copyright 2020 Acer Computer GmbH, Germany. All rights reserved. Acer and the Acer logo are registered trademarks of Acer Incorporated. Microsoft and Windows are registered trademarks of Microsoft Corporation. Intel and Pentium are registered trademarks of Intel Corporation. All other mentioned or otherwise recognizable trademarks, registered trademarks and/or service marks are the property of their respective owners. All prices quoted are recommended retail prices of the manufacturer