ViewSonic® MONITORS **VG2448**

Key **Features**

Seamless Viewing Experience | A More Comfortable Workspace | Environmentally Friendly Packaging | Convenient & Versatile Stand | Loaded with Connectivity

Product **Description**

Designed for the modern day office, the ViewSonic VG2448 monitor delivers an efficient end-to-end enterprise experience. Featuring SuperClear® IPS panel technology and 1080p resolution, this 24" (23.8" viewable) monitor delivers crisp and clear images from nearly any viewing angle. For enhanced productivity, an advanced ergonomic design offers a wide range of customizable adjustments for maximum comfort including pivot, swivel, height adjustment, and tilt. With the ability to tilt an impressive 40-degrees, the VG2448 is ideal for users who prefer to work while standing up, as well as for those who like to use their screen for group discussions. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features, making this monitor perfect for deployment in cloud-based environments.

1. Menu Controls
2. VESA Compatible Wall Mount 100 x 100 mm
3. USB 3.0 Type A (x2)
4. Kensington® Lock Slot
5. VGA
6. USB 3.0 Type B
7. USB 3.0 Type A (x2)
8. HDMI 1.4
9. DisplayPort In
10. AC In

24"
DISPLAY

IPS
PANEL

1920 x 1080
RESOLUTION

Contact Sales

call: 888.881.8781
email: salesinfo@viewsonic.com
visit: viewsonic.com

ViewSonic VG2448, 24 IPS Full HD Monitor

Display:

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS
Resolution:	1920 x 1080
Static Contrast Ratio:	1,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	WLED
Brightness:	250 cd/m2
Colors:	16.7M
Color Space Support:	6 bits
Aspect Ratio:	16:9
Response Time (Typical GTG):	14ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30,000
Panel Surface:	3H Anti-glare, hard-coating

Compatibility:

PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

Connector:

USB 3.0 Type A(4), USB 3.0 Type B(1), HDMI 1.4(1), Display Port(1)

Audio:

Internal Speakers:	2W (x2)

Power:

Eco Mode (Conserve):	14.6
Eco Mode (optimized):	17.4W
Consumption (typical):	25W
Consumption (max):	57W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5
Power Supply:	Internal

Additional Hardware:

Kensington Lock Slot:	1

Controls:

Physical Controls:	1,2, Up, Down, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104º F (0 - 40º C)
Humidity (non-condensing):	20-90%

Video Signal:

Frequency Horizontal:	24 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz

Video Input:

Analog Sync:	Separate Sync / Composite Sync / Sync on Green
Digital Sync:	TMDS for HDMI 1.4, PCI-E for DisplayPort

Ergonomics:

Height Adjust (mm):	130
Swivel:	120º
Pivot:	90º
Tilt (Forward/Back):	40º / 5º

Weight (imperial):

Net (lbs):	12.8
Net Without Stand (lbs):	7.6
Gross (lbs):	19.2

Weight (metric):

Net (kg):	5.8
Net Without Stand (kg):	3.4
Gross (kg):	8.7

Dimensions (imperial) (WxHxD):

Packaging (in.):	23.8 x 15.2 x 8.3
Physical (in.):	21.7 x 20.4 x 8.0
Physical Without Stand (in.):	21.7 x 12.8 x 2.0

Dimensions (metric) (WxHxD):

Packaging (mm):	604.0 x 385.0 x 210.0
Physical (mm):	549.4 x 517.0 x 202.2
Physical Without Stand (mm):	549.4 x 325.6 x 50.0

General:

Regulations: cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT Gold, UL-MX-CoC, Mexico Energy

PACKAGE CONTENTS: VG2448 Display, Power Cable, DP to DP Cable, USB 3.0 Upstream Cable, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907931112

Accessories:

CB-00008948, CB-00009950, CB-00010684, CB-00010958, LCD-CMK-001, LCD-WMK-001