# Product data sheet

Specifications



## APC NetShelter Rack PDU Advanced Switched Metered, 0U, 3 Phase, 415V, 69.0kVA 100A, 36 Outlets

APDU11550SM

## Main

| | |
|---|---|
| **Product or Component Type** | PDU |
| **Main Input Voltage** | 415 V AC 3 phase |
| **Input current limits** | 100 A |
| **Input Frequency** | 50/60 Hz |
| **Main Output Voltage** | 415 V AC 3 phase |
| **Input Connection Type** | IEC 309 100 A |
| **Number of power socket outlets** | 18 C13/C15/C19/C21<br>18C13/C15 |
| **PDU Type** | Switched metered outlet |
| **Protection Type** | Circuit breaker |
| **Number of rack unit** | 0U |

## Complementary

| | |
|---|---|
| **Mounting Location** | Front<br>Rear |
| **Mounting Mode** | Rack-mounted |
| **Mounting position** | Vertical |
| **Height** | 78.0 in (1980 mm) |
| **Width** | 3.3 in (85 mm) |
| **Depth** | 3.3 in (85 mm) |
| **Net Weight** | 45.6 lb(US) (20.7 kg) |

## Environmental

| | |
|---|---|
| **IP Degree of Protection** | IP67 |
| **Relative Humidity** | 5…90 % |
| **Storage Relative Humidity** | 5…95 % |
| **Ambient Air Temperature for Storage** | -4…140 °F (-20…60 °C) |
| **Storage altitude** | 0…50000 ft (0…15240 m) |
| **Operating altitude** | 0...10000 ft |
| **Ambient Air Temperature for Operation** | 23…140 °F (-5…60 °C) |

## Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304775645 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 91.3 in (232 cm) |
| **Package 1 Width** | 13.8 in (35 cm) |
| **Package 1 Length** | 6.5 in (16.5 cm) |
| **Package weight(Lbs)** | 58.4 lb(US) (26.5 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 36 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Better

#### Materials and Substances

| | |
|---|---|
| Average percentage of recycled plastic content | 15 % |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | 7547f066-9302-46d9-96e9-461928dd6901 |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. |
| PVC free | No |
| Silicon free | Yes |

### Use Longer

#### Lifetime extension

| | |
|---|---|
| Upgradeability | Yes |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

**Alternative**

