

Rittal – The System.

Faster – better – everywhere.

► Adaptor, 3 U Depth offset 100 mm – DK 7246.400

Date : Jun 24, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Adaptor, 3 U Depth offset 100 mm – DK 7246.400

created: 24.06.2021 on www.rittal.com/com-en



Product description

Description: This adaptor is used to recess 482.6 mm (19") mounting of equipment inside enclosures with 482.6 mm (19") installation in the foremost position, such as server or electronic enclosures. In this way, sufficient space can be gained in front of the mounting equipment to integrate patch panels or switches, whilst at the same time exploiting the maximum enclosure depth.

Material: Sheet steel

Surface finish: Zinc-plated

Supply includes: Assembly parts

Product description

Units: 3 U

Installation dimensions: Installation width: 482,6 mm / 19"

Packs of: 2 pc(s).

Weight/pack: 0.36 kg

Copper weight (kg per piece): 0

EAN: 4028177389830

Customs tariff number: 73269098

ETIM 7.0: EC002625

ETIM 6.0: EC002625

eCl@ss 8.0/8.1: 27189234

eCl@ss 6.0/6.1: 27189261

Product description: DK Adaptor 482,6 mm (19"), 3 U, Depth offset 100 mm

Approvals

Certificates: NA
