

Rittal – The System.

Faster – better – everywhere.

► CMC III CAN bus connection cable – DK 7030.092

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LÖH GROUP



CMC III CAN bus connection cable – DK 7030.092

created: 12.07.2021 on www.ittal.com/com-en



Product description

Description:	For connecting the PU to the CAN bus sensors III, units III and control units III as a bus, also for cabling together. Because it is available in different lengths, the CMC III system can be adapted to various applications and built to a custom design.
Applications:	For connecting the CAN bus units. Information and power transfer of the individual CAN bus units.

Product description

Dimensions:	Length: 1.5 m
Operating temperature:	Operation (environment): +0 °C...+55 °C
Ambient humidity (non-condensing):	Operation (environment): 5 % - 95 %
Interfaces/connections:	Connector (type): RJ45 Connector (type): RJ45
Packs of:	1 pc(s).
Weight/pack:	0.06 kg
Copper weight (kg per piece):	0
EAN:	4028177659438
Customs tariff number:	85444290

ETIM 7.0: EC000313

ETIM 6.0: EC000313

eCl@ss 8.0/8.1: 27189253

eCl@ss 6.0/6.1: 27189253

Product description: DK CMC III CAN bus connection cable, L: 1,5 m, type: RJ45

Approvals

Certificates: NA