



2m USB Type C to HDMI 8K60 Adapter Cable

Part No.: 43368

Description

- Connect a 8K HDMI display to your computer's USB Type C port*
- Supports HDMI resolutions up to 7680x4320@60Hz and 3840x2160@144Hz
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- Plug & Play, no drivers required
- 2 year warranty

This Lindy USB Type C to HDMI 8K60 Adapter Cable is a high performance solution, which allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort 1.4 Alternate Mode. The HDMI connector of the adapter cable can be directly connected to the HDMI display - while the 2m cable allows for a more flexible positioning of the HDMI display than when using a box converter - perfect for a simple and adaptable installation.

This cable supports resolutions up to 8K 7680x4320 60 Hz and 4K 144Hz** making it the ideal tool for 8K game streaming or high resolution 8K video editing. Additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, superior contrasts and a much wider colour gamut, for more lifelike colour. HDCP 2.2 ensures issue-free playback of 8K Ultra HD movies and other 8K content.

This cable is powered by the USB Bus, therefore no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV ecosystem with minimum difficulty, ideal for both professional and first time users.

*Please make sure your 8K TV settings are properly configured to HDMI 2.1 input.

**Please make sure that the source device supports DP 1.4 with DSC v1.2a

Technical details

Connectors

- Connector A: USB Type C Male
- Connector B: HDMI Type A Male
- Housing Material: Zinc Alloy
- Connector Plating: Gold plating
- Pin Construction: Copper Alloy
- Pin Plating: Gold plating
- Dimensions (approx.) WxDxH:
 - USB C: 30x10x5mm (1.80x0.39x0.2in)
 - HDMI: 60x20x8mm (2.36x0.79x0.31in)

Cable construction

- Length: 2m (6.56ft)
- Standard: HDMI 2.1
- Colour: Black
- Type: Round
- Jacket Diameter: 4.8mm (0.19in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 34AWG
- Shielding: Tinplate

Specifications

- Chipset: VMM7100
- Supported Bandwidth: 48Gbps
- Power Delivery: -
- Maximum Resolution: 7680x4320 60Hz, 3840x2160 144Hz
- Nominal Attenuation: 100MHz-10GHz $\leq$ 24dB
- Minimum Bend Radius: 28.8mm (1.13in)
- Operating Temperature: -20°C - 40°C (-4°F - 104°F)
- Storage Temperature: -40°C - 80°C (-40°F - 176°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & UL, CP65

Purchasing information

- No.: 43368
- EAN: 4002888433686

This product is also available in other lengths:

- 43367 - 1m (3.28ft)
- 43368 - 2m (6.56ft)