

# Eaton EVMIF332X

Catalog Number: EVMIF332X

Eaton Metered Input G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 42 outlets (24)C13, (18)C39

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Rack PDU G4	EVMIF332X
<b>Model Code</b>	<b>EAN</b>
PDU G4 MI 0U 309 32A 3P 24xC13,18xC39	3553340697159
	<b>Product Length/Depth</b>
	1730 mm
<b>Product Height</b>	<b>Product Width</b>
53 mm	52 mm
<b>Product Weight</b>	<b>Compliances</b>
5.5 kg	CB LVD Directive RoHS Directive WEEE Directive Packaging Directive EMC Directive

## Certifications

IEC 62368-1  
EN IEC 63000  
CISPR 35/EN 55035  
CE  
EAC  
UKCA  
Cm  
Ukr  
IEC/EN 61000-6-2  
IEC/EN 61000-6-4  
IEC 61000-3-11  
IEC 61000-3-12

### Special features

Remote Site Management  
Versatile C39 outlet  
supports C14 or C20 power cord plug  
High retention outlets  
designed to securely fit standard power cords and support P-Lock power cords  
Cybersecurity standards UL 2900-1 and IEC 62443-4-2  
Hot-Swap network control module  
Network Cascading, connect up to 32 PDUs via network loop  
Power sharing between two network modules PDUs ensures constant access to PDU data & sensors  
1% IEC Class 1 billing grade measurement accuracy  
Gigabit network card with 2x Gb ports  
Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS  
Optional sensor  
Temperature/Humidity

### Type

Metered input Rack PDU

### Form factor

0U (Vertical)

### Outlet control

No

### Accessories

Rack PDU  
Rack mounting accessories  
Quickstart guide  
Safety Instructions

### Operating Temperature

### Brochures

[Rack PDU G4 Brochure EN](#)

### Declarations of conformity

[EU declaration of conformity Rack PDU G4](#)

0° to 60°C (32° to 140°F)

Mounting direction

Vertical

Color

Black

Material

Aluminium

Input connection

IEC-60309 32A 3Ph

Cord length

3m

Wattage

22 kW max

Amperage Rating

32 A

Input voltage

240/415V

Phase

Three-phase

Frequency rating

50/60 Hz

Outlets

(24) C13, (18) C39

Number of Outputs C13

24

Number of Outputs C19

18

Number of outputs (other)

18

Number of outlets with earth pin

42

Circuit breaker

(6) single-pole

SNMP

Yes

Ethernet interface

Yes

Serial interface

Yes

Mass configuration

Yes

Electrical connection

Connecting cord with plug

Evaluation

At distance

Mounting Dimension (metrical)

52

Mounting dimension (standardized)

Metric

Switchable

No

Over voltage category

2

Series

G4



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)