


Thermal Printer

SLP600 Series



SLP620

- 300 dpi (650/650SE), 203dpi (620)
- 100mm/s (650/650SE), 70mm/s (620)
- USB (650/620), Serial and USB (650SE)

Model		SLP 620	SLP 650/650SE
Printing	Method	direct thermal	
	Resolution dpi (dots/mm)	203 (8)	300 (11.81)
	Paper width (mm) max	57.9	
	Printing width (mm) max	48	48.8
	Speed (mm/s)	70*	100*
Barcode		Code39, I-2 of 5, Code128, EAN13, EAN128, UPC-A, UPC-E, Codabar, Maxi Code, PDF417, Data Matrix, QR Code	
Communication Interface		USB	650 USB / 650SE USB, RS-232C
Power Supply (V) DC		5.7 to 6.3	11.4 to 12.6
Current consumption (A)	Normal	2.3	2.8
	Maximum	2.5	3.0
Service life	Abrasion resistance (km)	6	15
Operating temperature (°C)		5 to 40	
Storage temperature (°C)		-20 to 60	
Dimensions (W x D x H mm)		113.8 x 172.0 x 148.0	
Mass (g)		ca. 490	
Software		Windows® 2000, 2003, XP, Vista, 7 / Mac OS X	



SLP650

SLP650SE



Specifications are subject to change without notice.

