



LCD DISPLAY

VG3209-4K

Key Features

- 4K UHD 3840 x 2160 resolution
- SuperClear® IPS panel
- Height-adjustable swivel stand with tilt function
- HDMI and Display Port inputs for simple connectivity
- HDR10 Delivers Stellar Contrast



Product Description

The ViewSonic VG3209-4K is a 32" UHD monitor featuring HDMI and Display Port inputs for business and home use. The eye-care technology presets to cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.

Visit Us

www.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	350 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 91% size (Typ) sRGB: 128% size / 99% coverage (Typ)
Pixel Size:	0.182 mm (H) x 0.182 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	2
Power in:	DC Socket (Center Positive)

AUDIO

Internal Speakers:	2.5Watts x2
--------------------	-------------

POWER

Eco Mode (Conserve):	25W
Eco Mode (optimized):	33W
Consumption (typical):	40W
Consumption (max):	42W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

Cable Organization: Yes

CONTROLS

Physical Controls: Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)

On Screen Display: Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature: 32°F to 104°F (0°C to 40°C)

Humidity (non-condensing): 20% to 90%

WALL MOUNT

VESA Compatible: 100 x 100 mm

INPUT SIGNAL

Frequency Horizontal: HDMI (v2.0): 15 ~ 140KHz, DisplayPort (v1.4): 24 ~ 140KHz

Frequency Vertical: HDMI (v2.0): 24 ~ 75Hz, DisplayPort (v1.4): 48 ~ 75Hz

VIDEO INPUT

Digital Sync: TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)

ERGONOMICS

Height Adjust (mm): 90

Swivel: 360°

Tilt (Forward/Back): -4° / 20°

WEIGHT (IMPERIAL)

Net (lbs): 19.6

Net Without Stand (lbs): 14.8

Gross (lbs): 24

WEIGHT (METRIC)

Net (kg): 8.9

Net Without Stand (kg): 6.7

Gross (kg): 10.9

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.): 34.1 x 19.8 x 5.7

Physical (in.): 28.1 x 18.47~22.01 x 7.9

Physical Without Stand (in.): 28.1 x 16.8 x 2.3

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm): 865 x 503 x 144

Physical (mm): 714 x 469~559 x 202

Physical Without Stand (mm): 714 x 428 x 59

GENERAL

Regulations: Energy Star, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA

PACKAGE CONTENTS: VG3209-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1

Recycle/Disposal: Please dispose of in accordance with local,

state or federal laws.

Warranty:

*Warranty offered may differ from market to market

Power Management:

Energy Star standards

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.