

Product datasheet

Specifications



APC Back-UPS 950VA, 230V, AVR, 4 Schuko outlets

BX950MI-GR

Overview

Lead time

Main

Main Input Voltage	230 V
Rated power in W	520 W
Rated power in VA	950 VA
Nb of power socket outlets	4 Schuko
Cable length	1.22 m
Number of cables	1
Battery type	Lead-acid battery

General

Provided equipment	user manual
Max runtime	120 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	16 cm
Width	12 cm
Depth	35.5 cm
Net weight	6.1 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V
Input Power Factor at Full Load	0.54

Output

Maximum configurable power in W	520 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Full load runtime	00:01:00 480 W
Half load runtime	00:06:30 240 W
Maximum configurable power in VA	950 VA
Transfer time	6 ms typical : 10 ms maximum


Conformance

Product certifications	CE CB EAC
Standards	EN/IEC 62040-1 EN/IEC 62040-2 CE
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery power in VAh	97 VAh runtime 108 VAh capacity
Battery life	3...5 year(s)
Replacement battery	RBC17 

Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
-------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Extended runtime	0
-------------------------	---

Communications & Management

Control panel	LED Status display with on line : on battery
----------------------	----------------------------------------------

Alarm	Alarm when on battery : distinctive low battery alarm
--------------	-------------------------------------------------------

Surge Protection and Filtering

Surge energy rate	273 J
--------------------------	-------

Data line protection	RJ45 10/100/1000 Base-T Ethernet protection
-----------------------------	---------------------------------------------

Packing Units

Package 1 Weight	6.6 kg
-------------------------	--------

Package 1 Height	25 cm
-------------------------	-------

Package 1 Width	19.7 cm
------------------------	---------

Package 1 Length	43 cm
-------------------------	-------

SCC14	10731304410857
--------------	----------------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
--------------------------	--------------------------------------------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------