



USB Type C to Dual Display Converter, MST Hub

No.: 43304

Connect an HDMI and a DP display simultaneously

Description

- Connects an HDMI and Displayport display simultaneously to a USB Type C device
- Requires DisplayPort Alternate support from the USB Port/Bus
- Supports resolutions up to 3840x2160@60Hz for one display and 3840x2160@30Hz for simultaneous use*
- Plug and Play, no drivers required
- 2 year warranty

USB Type C to Multi-AV converters allow users to connect multiple AV interfaces to a USB C equipped device. The Lindy USB Type C to Dual Display Converter allows users to connect a high definition HDMI and/or DisplayPort display to a Macbook, ultrabook or notebook with USB DisplayPort Alternate Mode.

The Converter can send the same display information to two screens with SST technology or use both screens as individual displays with separate display information using MST functionality, this is easily configured using the display settings of your computer.

Installation is simple as no drivers are required, while Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

*Please note that some AMD GPUs and 8th generation Intel NUCs do not support two native 4K displays.

Technical details

Specifications

- AV Interface: USB Type C to HDMI & DisplayPort
- Interface Standard: HDMI 2.0, DP 1.2
- Supported Bandwidth: 21.6Gbps
- Maximum Input Resolution: 3840x2160@60Hz
- Maximum Output Resolution: 3840x2160@60Hz; 3840x2160@30Hz [2 displays simultaneously]
- Chipset: STDP4320
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: -
- HDCP Support: HDCP 1.3
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode, SST & MST support

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x HDMI (Female), 1 x DP (Female)
- Power: Bus-powered

Physical Properties

- Dimensions (approx.) WxDxH: 67.8x63x17mm [2.67x2.48x0.67in]
- (Fixed) Cable Length: 232mm [9.13in]
- Housing Material: ABS
- Net Weight: 0.053kg [0.12lb]
- Operating Temperature: 0°C - 45°C [32°F - 113°F]
- Storage Temperature: -10°C - 70°C [-4°F - 158°F]
- Humidity: 0% - 90% RH (non-condensing)
- Power Requirements: -
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 176x194x20mm [6.93x7.64x0.79in]
- Gross Weight: 0.065kg [0.14lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH, CP65

Package Contents

- USB Type C to Dual Display Converter

Purchasing information

- No.: 43304
- EAN: 4002888433044