

2x1 HDMI + VGA to HDMI Converter Switch w/ Automatic and Priority Switching - 1080p

Product ID: VS221VGA2HD



The VS221VGA2HD HDMI & VGA Auto Switch lets you connect an HDMI and a VGA audio/video source to the same HDMI display or projector, and automatically or manually switch between which video source is displayed. The multi-input A/V switch supports video resolution up to 1920x1200 (1080p) and includes mounting hardware for a tidy professional installation.

The A/V switch features built-in VGA conversion, enabling you to connect an HDMI and a VGA video source to the same HDMI display without the use of additional adapters or scalers.

The VS221VGA2HD ensures hassle-free operation with two different auto switching modes: automatic switching that detects and selects a newly connected device, as well as priority selection which lets you choose which port should be activated by default for automatic switching.

This A/V switch has been designed with the boardroom and classroom in mind: the VS221VGA2HD features VGA and HDMI inputs to support a wide range of devices, and the built-in converter makes it easy to connect to the room's display without the use of additional adapters. Plus, automatic switching encourages on-the-fly collaboration among students or co-workers, by making it easy to share your projector between multiple source devices.

If you are looking for a similar device with VGA output, please see our VS221HD2VGA.

The VS221VGA2HD is TAA compliant and backed by a StarTech.com 2-year warranty, and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

· Automatically switch between your set top box or computer in a home theatre environment



- Share a classroom or conference room projector with VGA and HDMI video sources
- Connect and switch between VGA and HDMI video sources on a test bench, for troubleshooting computers
- Switch between VGA and HDMI video sources on your digital signage display in hospitals, shopping centers, or schools

Features

- Accommodates both VGA and HDMI input devices in a single switch with HDMI output, saving hassle and expense by reducing the need for adapters
- Effortless control with automatic and priority port selection
- Ideal for classroom and boardroom display applications, allowing presenters to connect a wide range of devices
- Supports video resolutions up to 1920x1200 / 1080p
- Mounting hardware included

Hardware		
	Warranty	2 Years
	Ports	2
	AV Input	НДМІ
		VGA
	AV Output	НДМІ
	Audio	Yes
Performance		
	Maximum Analog Resolutions	1920x1200
	Maximum Digital Resolutions	1920x1200
	Supported Resolutions	Supports resolutions up to 1920x1200 / 1080p
	Wide Screen Supported	Yes
	Audio Specifications	2-channel 3.5mm stereo audio (VGA)
		7.1 surround sound (HDMI)

Connector(s)



Connector A HDMI (19 pin)

VGA (15 pin, High Density D-Sub)

3.5 mm Mini-Jack (3 Position)

Connector B HDMI (19 pin)

Indicators

LED Indicators VGA Port Selected

HDMI Port Selected

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 0.4 A

Output Voltage 5 DC

Output Current 1 A

Power Consumption (In

Watts)

Environmental

Operating Temperature 0C to 40C (32F to 104F)

5

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 0%~80%

Physical Characteristics

Material Steel

Product Length 4.0 in [10.2 cm]

Product Width 2.1 in [54 mm]

Product Height 1.1 in [29 mm]

Weight of Product 8.0 oz [226 g]

Packaging Information



Package Length 6.2 in [15.7 cm]

Package Width 9.3 in [23.6 cm]

Package Height 2.5 in [64 mm]

Shipping (Package) Weight

23.2 oz [657 g]

What's in the Box

Included in Package VGA+HDMI to HDMI converter switch

mounting kit

universal power adapter (NA, EU, UK, ANZ)

instruction manual

^{*}Product appearance and specifications are subject to change without notice.