


3 inch Mobile Printer

MP-B30L



- Ultra Small Mobile Label Printer
- Compact & Light Weight
- Drop rating: 1.8m(6feet), IP rating: IP54
- Printing Speed: 130mm/sec max
- Simple Operation & Stylish Design
- Option Cradle for Charging



MP-B30L



Model	MP-B30L
Method	Thermal line dot printing
Number of dots/line	576
Resolution (dots/mm)	8
Paper width (mm)	80 ⁺⁰ ₋₁ / 76.2 ⁺⁰ ₋₁ / 58 ⁺⁰ ₋₁
Printing width (mm)	72
Printing speed (mm/sec) max	130
Outside diameter of paper roll (mm)max	Φ51
Character matrix (HxW dots)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of paper	Roll paper, Label roll paper
Character type	Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Barcode	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128,PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, AZTEC
Power supply	Li-ion Battery
Communication interface	USB, Bluetooth®, W-LAN **
Input buffer	4K bytes
Command	ESC/POS™ conformity, ZPL II™ conformity, CPCL conformity
Cutting method	Tear bar
Falling resistance	1.8m ^{*2}
IP rating	IP54 ^{*2}
Operating Temperature (°C)	-20 to 55
Service life: Abrasion resistance (km)	50 ^{*3}
Dimensions (W×D×Hmm)	105 x 126 x 58 ^{*4}
Mass (g)	395 ^{*5}
Standard	FCC, CE, VCCI
Bundled item	AC adapter, Battery, USB cable, Belt clip
Option	Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case
Software	Printer driver, OPOS, POS for .NET, Windows® CE(SDK), Android™(SDK), iOS SDK, Xamarin SDK, URL Print Agent

^{*1} Selected model. ^{*2} This number is test result based on SII procedures, not guaranteed value. ^{*3} Use recommended thermal papers. ^{*4} Excluding protrusion ^{*5} with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP.
Windows® is the registered trademark of Microsoft Corporation(USA).
Android™ is a trademark of Google Inc.

Official site <https://www.sii-ps.com>

Printed in Jun. 2021



Seiko Instruments Inc.
Print System Div.
8, Nakase 1-chome, Mihama-ku
Chiba-shi, Chiba 261-8507, Japan
Telephone: +81-43-211-1106 Facsimile: +81-43-211-8037

Seiko Instruments U.S.A., Inc.
21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.
Telephone: +1-310-517-7778 Facsimile: +1-310-517-7779

Seiko Instruments GmbH
Siemensstrasse 9 D-63263 Neu-Isenburg, Germany
Telephone: +49-6102-297-0 Facsimile: +49-6102-297-222
E-mail : info@seiko-instruments.de

Seiko Instruments Trading (H.K.) Ltd.
4-5 / F, Wyler Center 2, 200 Tai Lin Pai Road, Kwai Chung,
N.T., Kowloon, Hong Kong
Telephone: +852-2494-5160 Facsimile: +852-2424-0901

Seiko Instruments Taiwan Inc.
2F., No. 143, Changchun Rd.,
Taipei, Taiwan R.O.C.
Telephone: +886-2-2563-5001 Facsimile: +886-2-2563-5580