

Product datasheet

Specifications



Rack PDU, Metered, Zero U, 10A, 230V, (16) C13

AP7850B

Overview

Lead time

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit

Physical

Colour	Black
Height	124.5 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	3.07 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Permissible voltage	200...250 V
Max line current	10 A
Load capacity	2300 VA
Network frequency	47...63 Hz

Output

Number of power socket outlets 16 IEC 60320 C13

Conformance

Product certifications CE
GOST
VDE

Environmental

Ambient air temperature for operation -5...45 °C

Relative humidity 5...95 %

Operating altitude 0...10000 ft

Ambient air temperature for storage -25...65 °C

Storage Relative Humidity 5...95 %

Storage altitude 0.00...15240.00 m

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 213.4 cm

Package 1 Width 32.3 cm

Package 1 Length 38.7 cm

Package 1 Weight 3.98 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Lead free Yes

Mercury free Yes

RoHS exemption information [Yes](#)

Optimized Energy Efficiency Energy efficient product

Take-back Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)