ProLite XCB3492WQSNPH-B1

INFORMATION




34’’ IPS UWQHD curved monitor with Windows Hello camera, USB-C Dock, LAN, KVM and 15cm height-adjustable stand

The 34" XCB3492WQSNPH is designed for a smooth and efficient workspace. The gently curved 3800R IPS panel offers expansive 3440x1440 screen space, consistent colours and wide viewing angles for a comfortable, natural viewing experience.

Connect a laptop through the USB-C dock, switch easily between two computers with the built-in KVM and stay connected via LAN. DisplayPort-out supports daisy chaining for an easy multi-monitor setup, while the 5MP autofocus webcam with Windows Hello, 15cm height-adjustable stand and eye-care technologies help keep everyday work comfortable and productive.

FEATURES



Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.




USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable — handle video, data, and power while keeping your desk clean and organized.



Easy access with Window Hello cam

Log in quickly and securely with facial recognition, while enjoying crystal-clear video calls thanks to the high-resolution autofocus webcam.



Expand your workspace with a dual monitor setup

Pair your 34-inch ultrawide monitor with a 24-inch vertical monitor to create an efficient dual screen workspace. Use the ultrawide display for your main tasks while the portrait monitor keeps emails, Teams, dashboards, market data, documents or monitoring tools visible at a glance.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	34", 86.7cm
Panel	IPS LED, matte finish
Curved	3800R
Native resolution	3440 x 1440 @100Hz (4.9 megapixel UWQHD)
Aspect ratio	21:9
Panel brightness	350 cd/m²
Static contrast	1500:1
Advanced contrast	80M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 160kHz
Viewable area W x H	799.8 x 334.8mm, 31.5 x 13.2"
Pixel pitch	0.233mm
Frame Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0) DisplayPort x1 (v.1.4) USB-C x1 (PD 95W)
Signal output	DisplayPort x1 (Daisy Chain MST max. 3440x1440)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, DP out, USB v.3.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1

03 FEATURES

KVM switch	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	Built-in 5MP webcam with autofocus, microphone and privacy shutter compliant with Windows Hello, Eye Comfort
HDR	ready, HDR10
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA

Control buttons	Navigation Button, Power, (Center: MainMenu/Execution), Front (Move Down/Submenu), Rear (Move Up/Input Select), Left (Move Left/Volume Down), Right (Move Right/Volume Up)
User controls	picture adjust (brightness, contrast, Eco, HDR, ACR, Adpative Sync, X-res technology, black tuner), colour settings (6-axis, i-Style colour, gamma, RGB range, colour temp., user preset), PiP/PbP (PiP/PbP mode, sub source, PiP position, PiP size, swap, audio input), OSD (H. position, V. position, time, background, display information, MAC address), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB-C speed, USB charge, KVM, DDC/CI control, MST DP-out), input select, audio settings (volume, mute audio), recall
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.5m), DP (1.8m), USB-C (1.0m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	31W default, 0.5W stand by, 0.3W off mode


07 SUSTAINABILITY

Regulations	CE, TÜV-GS, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA, TCO Edge
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead, Lead monoxide, Diboron trioxide

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	816.5 x 453 (602) x 245.5mm
Box dimensions W x H x D	910 x 480 x 160mm

Weight (without box)	9.8kg
Weight (with box)	14.4kg
EAN code	4948570127894



GALLERY

























All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**