DATASHEET

Epson ELPCB01 Control and Connection Box



Put your Epson projector's functions at your fingertips with the Epson ELPCB01 Control and Connection Box, which works with all Epson education projectors and the ELP-DC06 USB visualiser.

Simply plug your Epson projector and signal sources such as computers or DVD players into the wall-mounted connection box, and enjoy the convenience of having your projector controls within easy reach. No more fiddling with ceiling-mounted inputs or remote controls – you can switch between sources at the touch of a button, saving valuable teaching time.

The ELPCB01 keeps cables neat and tidy, improving the look of your classroom and minimising trip hazards with the included cable cover. It also boosts the USB signal so USB cables can be extended up to 10 metres.

Allowing you to focus on the lesson rather than your equipment, the ELPCB01 is straightforward to use, with large buttons and clearly-labelled inputs. Outwards-opening doors make accessing the inputs a one-handed job. All inputs and buttons are identical to those on Epson's projectors for easy recognition.

Complete your total audio visual solution by connecting the optional Epson 2 x 15W active speakers for high-quality sound.



KEY FEATURES

- Keep cables neat and tidy
- USB booster allows USB cable extension up to 10 metres
- Straightforward to use with large buttons
- Clearly-labelled inputs are easy to access
- Buttons and inputs identical to those on Epson projectors



Without the Epson ELPCB01 Control Box



With the Epson ELPCB01 Control Box








PRODUCT SPECIFICATIONS

	Control & Connection Box - ELPCB01
I/O PORT Input video	2 x D-sub 15-pin, 1 x composite video, 1 x S-Video, 1 x HDMI, 1 x USB 2.0 type A, 1 x USB 2.0 type B
Input audio Output video	4 x Stereo mini jack, 1 x RCA (white/red) 2 x D-sub 15-pin, 1 x Composite video, 1 x S-Video, 1 x HDMI, 1 x USB 2.0 type A, 1 x USB 2.0 type B
Output audio Control	1 x Stereo mini jack, 1 x RCA (white/red) 1 x RS232C
FUNCTION Power Switch Projector power Source selection A/V mute Audio mute Volume	On/off Yes Computer1 / Computer2 / Video / S-Video / USB(A/B) / HDMI / LAN Yes Yes
POWER Power voltage Power consumption (normal / standby)	12V DC (AC adapter AC/DC 100V-240V AC/DC, 50/60Hz) < 8W / < 0.5W
GENERAL Operating temperature Operating humidity Dimensions (W x D x H) Weight	5 °C to 35 °C <41 °F to 95 °F> 20%-80% RH 285 × 100 × 173.7mm 1.7kg

Epson ELPCB01 Control and **Connection Box**

OPTIONAL ACCESSORIES

• ELPSP02 Active Speakers (x2)



Speakers, projector and Control Box typical installation.



2 x 15W active speakers for high-quality sound

	Speakers - ELPSP02 (optional accessory)	
ACTIVE SPEAKER (incl. amplifier)(left) Output power Frequency response Driver Bass reflex port SPL Enclosure Material Impedance Control Input Output	15W at 10% T.H.D 80Hz - 20KHz Tweeter / woofer One port 100dB at 1W at 1m Plastic 8 ohms 1x volume knob, 1x power switch, 1x rocker switch, 1x treble adjustment control, 1x bass adjustment control, 1x AC select switch DC in, mini Jack φ 3.5mm, RCA pin jack (left and right) RCA pin jack (to passive speaker), mini jack φ 3.5mm	
PASSIVE SPEAKER (right) Output power Frequency response Driver Bass reflex port SPL Input	15W rms 80Hz - 20kHz Tweeter / woofer One port 100dB at 1W at 1m PCA pin jack (right) from active speaker	
POWER Power Voltage Power Consumption (Stand-by mode)	18V DC (AC adapter AC/DC 100V-240V AC/DC, 50/60Hz) <0.7W	
GENERAL Operating temperature Operating humidity Dimensions (W x D x H) Weight	5°C to 35°C (41°F to 95°F) 20% - 80% RH 156 x 141 x 230mm 2.1kg (left) & 1.9kg (right)	

PRODUCT LOGISTICS

	Control & Connection Box	Speakers (optional accessory)
MODEL	ELPCB01	ELPSP02
SKU CODE		
BARCODE		
WHAT'S IN THE BOX	ELPCB01, 1x power cable, 1x external AC power adater, 1x cable cover, 1x pen holder, 1x user's guide, 1x installation manual set	2x speakers, 1x power cable, 1x external AC power adater, 2x plastic mounting units for speakers, 2x screws, 1x mounting blacket for AC adapter, 1x user's guide, 1x speaker cable
GROSS WEIGHT	3.3kg	11.7kg
CARTON DIMENSIONS (L x W x H)	310 x 310 x 190mm	415 x 375 x 325mm



For further information please contact your local Epson or ce or visit www.epson-europe.com

For further information please contact your local Epson o° ce or visit www.epson-europe.com Austria'0810/20°10'13 (0,07 c/min)Belgium°070/350120 (0,1735 c/min) Czech°800/142°052Denmark°44°50°85°85°8Finland°0201°552°091 France°0974″55°04°04 (Cost of local call, opator charges may apply) Germany°01805/23°41°10 (0,14 c/min aus dem dt. lēstnetz, Mobilfunkpreise abweichend, Ab 1.3.2010 Mobilfunkpreis max. 0,42 c/min) Greece°210-809499 Hungary°06800°147°83/reland°01°436°774724taly°02-660321°10° (0,12°c/min) Luxemburg°900/43010°(0,24°c/min) Middle East°+9714°8818934Netherland*0900-5050808 (0.05°c/opcep°+°0.15°c/min) Norway°+47°67°11°37°00Poland°0-0-800′4911299 (0,16°z/min)Portugal″707°222°111Russia°(059°777-03-55Slovakia°0850°111°429 South Africa°(+2711)°465-9621Spain°93°582°15°00Sweden°0771-400135 (Mobilsamtal°=°0,99°kr/min, bkala samtal°=°0,30°kr/min, Utlandssamtal°=°0,89°kr/min)Switzerland*0848°448820 (8°cent./min)Turkey°(0212)°3360303United'Kingdom°0871°222°6702

EPSON[®]