# Specifications



Photo is representative





## Eaton MBP11KIG2

Eaton HotSwap MBP Gen2 maintenance bypass, 11000 VA, Input: Hardwired, Outputs: (4) C39, Hardwired, Rack-mounting kit included

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton HotSwap MBP maintenance bypass |
| **CATALOG NUMBER** | MBP11KIG2 |
| **MODEL CODE** | Eaton HotSwap MBP 11000i G2 |
| **EAN** | 3553340684753 |
| **PRODUCT LENGTH/DEPTH** | 130 mm |
| **PRODUCT HEIGHT** | 130 mm |
| **PRODUCT WIDTH** | 285 mm |
| **PRODUCT WEIGHT** | 4.6 kg |
| **WARRANTY** | 2 year |
| **COMPLIANCES** | LVD Directive (CB)<br>EMC Directive<br>RoHS Directive<br>REACH<br>WEEE Directive<br>Packaging Directive |
| **CERTIFICATIONS** | IEC/EN 62040-1<br>IEC/EN 62040-2<br>IEC/EN 62040-3<br>CE<br>UKCA<br>Cm<br>Ukr<br>RCM |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **RACK SIZE** | 3U |
| **CONSTRUCTION TYPE** | 482.6 mm (19 inch) device |
| **RACK MOUNTING KIT** | Yes |
| **PACKAGE CONTENTS** | • Maintenance Bypass<br>• Rack mounting kit<br>• Quick start guide |
| **TYPE OF ACCESSORY** | Bypass |
| **USED WITH** | 9PX Gen2 (8/11KVA) / 9SX Gen2 (8/11KVA) |
| **RECEPTACLE** | (4) C39 |
| **NUMBER OF OUTPUTS HARDWIRED** | 1 |
| **TEMPERATURE RANGE** | 0° to 40°C (32° to 104°F) |

## Resources

| | |
|---|---|
| MANUALS AND USER GUIDES | eaton-9px-mbp-gen2-advanced-user-guides-en-us.pdf |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.