


# ProArt Display PA328CGV



## Key Features



**WQHD**  
**2560x1440**

Supporting WQHD 2560 x 1440 resolution for crystal clear image quality



Up to 600 nits brightness with HDR for lifelike contrast & color that brings out details like never before



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle

**165 Hz**  
Rapid Refresh Rate

Decimating blurry and delivers smooth and crisp video rendering



Up to 95% DCI-P3 international color standard of digital cinema industry



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the  $\Delta E$  color difference value is less than 2



USB-C connection for DisplayPort, USB data transmission and supports 90W power delivery



Desk Mount Kit

A convenient mounting clamp is included to help free up desk space




4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

# ProArt Display PA38CGV

## Spec Sheet

<b>Display</b>	<p>Panel Size : 32-inch (81.28cm) Wide Screen (16:9)          Display Viewing Area(HxV) : 708.48 x 398.52 mm          Panel Backlight / Type : IPS          True Resolution : 2560 x 1440          Pixel Pitch : 0.277 mm          Display Colors : 1073.7M (10 bit)          Color Saturation : 95% DCI-P3, 100% sRGB/Rec. 709          Brightness : 450 cd/m<sup>2</sup> (typical), 600 cd/m<sup>2</sup> (peak)          Contrast Ratio: 1000:1 (typical)          ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1          Viewing Angle (CR≥10) : 178°(H)/178°(V)          Response Time : 5ms (GTG)          Flicker-free : Yes          HDR support : Yes, HDR-10          Refresh Rate (Max) : 165Hz</p>
<b>Video Feature</b>	<p>Trace Free Technology : Yes          ProArt Preset : 10 modes (Standard / sRGB / Rec. 709 / DCI-P3 / Rapid Rendering / HDR / Scenery / Reading / User mode1 / User mode2)          Color Accuracy : <math>\Delta E &lt; 2</math>          ProArt Palette : Yes          Gamma Adjustment : Yes (Support Gamma 2.6, 2.4, 2.2, 2.0, and 1.8)          Color Adjustment : 6-axis (R, G, B, C, M, Y)          Color Temperature Selection : 5 modes          Picture-in-Picture : Yes          Picture-by-Picture : Yes (support up to 2 windows)          QuickFit+ : Yes (Center Marker / Safety Area / Ruler / Customization)          HDCP support : Yes, 2.2          FreeSync Premium Pro support: Yes (48 ~ 165Hz)</p>
<b>Audio Feature</b>	<p>2W x 2 stereo, RMS</p>
<b>IO ports</b>	<p><b>Signal Input :</b>          DisplayPort 1.4 x 1          HDMI (v2.0) x 2          USB-C x 1 (90W PD)</p> <p><b>Earphone Jack :</b>          Yes (3.5mm Mini-jack)</p> <p><b>USB Hub:</b>          4x USB 3.2 Gen 1 Type-A</p> 
<b>Signal Frequency</b>	<p>Digital Signal Frequency : HDMI: 30~222 KHz (H) / 48~144 Hz (V)          USB-C, DisplayPort: 30~250 KHz (H) / 48~165 Hz (V)</p>
<b>Power Consumption</b>	<p>Power On (Typical): &lt;28W          Power Saving Mode : &lt; 0.5W ; Power Off Mode : 0.5W (Hard Switch)          100-240V, 50/60Hz</p>
<b>Mechanical Design</b>	<p>Tilt : +23° ~ -5°          Swivel : +30° ~ -30°          Pivot : 90° (Clockwise&amp; Anticlockwise)</p> <p>Height Adjustment : 0 ~ 130 mm          VESA Wall Mounting : 100 x 100 mm          Desk C-Clamp Support</p>
<b>Dimensions</b>	<p>Phys. Dimension with Stand (WxHxD) : 727.08 x (471.48~601.48) x 245 mm          Phys. Dimension without Stand (WxHxD) : 727.08 x 428.13 x 67.72 mm          Box Dimension (WxHxD) : 840 x 516 x 280 mm</p>
<b>Weight</b>	<p>Net Weight (Esti.) : 11.7 Kg, Without Stand (Esti.) : 7.15 Kg,          Gross Weight (Esti.) : 16.8 Kg</p>
<b>Accessories</b>	<p>Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), USB-C to USB-A cable (optional), Desk C-Clamp, Calibration Report, Quick Start Guide, Warranty Card, Welcome Card</p>
<b>Compliance Standard</b>	<p>Energy Star®, FCC, UL/cUL, cTUVus, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, CECP, BSMI, Taiwan Energy Label, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, SDcC, e-Standby, PSB, BIS, VN MEPS, TCO, RoHS, NOM, CEC, WHQL Windows 7/8.1/10, EPEAT Bronze, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified, VESA DisplayHDR 600</p>

\* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

\*\*All specifications are subject to change without notice