



2 Port Dual Head DisplayPort 1.2 KVM Switch

No.: 39306

Control Two Dual Head DisplayPort PC's from a single Control Console

Description

- Provides control of two DisplayPort equipped computers using a keyboard, mouse & two displays
- Ultra-high definition resolutions of up to 3840x2160@60Hz provide exceptional visual performance
- Compatible with various USB devices including printers, storage devices and human interface devices (HID) such as mice and keyboards
- Switch between host PC's with ease with an IR remote control or front panel button
- 2 Year warranty

The Lindy 2 Port Dual Head DP 1.2 KVM Switch is a powerful, compact solution for providing access and control over two dual head, DisplayPort equipped PCs using a single set of peripherals and displays. Four USB 2.0 ports allow for the connection and sharing of USB peripherals & storage devices between host PC's seamlessly.

Supporting the highest, practical, digital video resolutions up to 3840x2160@60Hz on two displays simultaneously, this switch is ideal for the most demanding office based tasks such as computer-aided design, videography, rendering and more, only made possible by its proficiency in outputting a combined resolution of 7680x2160.

Support for a wide-range of USB devices ensure maximum compatibility with existing keyboards, mice, headsets, printers and more, virtually guaranteeing integration of the switch in existing environments will be completely hassle-free. Female DisplayPort connectors provide flexibility and hands the user jurisdiction to use existing cabling in appropriate lengths.

Installation within new & existing set-ups is uncomplicated, thanks in part to its small form factor, as well as the pre-installed mounting hardware. An industrial, locking DC power connector provides peace of mind as accidental disconnections are almost impossible, perfect for mission critical medical or manufacturing applications.

Please Note: connection cables are not included

Technical details

Specifications:

- AV Interface: DisplayPort
- Console Interfaces: USB
- Interface Standard: DisplayPort 1.2, USB 2.0
- Maximum Resolution: 3840x2160@60Hz
- HDCP Support: 1.4 & 2.2
- Supported Audio: Pass-through

- Separate Audio Ports: -
- Serial Interface: -
- Console Number: 1
- Max Number PC/Server: 2
- Cascadable: -
- Switching Method: Push Button / IR Remote Control
- 19" Rack Mountable: -
- Special Features: Dual Head

Connectors:

- Console Interfaces: 2 x DisplayPort 1.2 (Female), 4 x USB Type A (Female)
- PC/Server Interfaces: 4 x DisplayPort 1.2 (Female), 2 x USB Type B (Female)
- Other Interfaces: -
- Power: DC5V 5.5/2.5mm

Physical Properties:

- Dimensions (approx.) WxDxH: 184x35x60mm (7.24x1.38x2.36in)
- Housing Material: Metal
- Net Weight: 0.674kg (1.48lb)
- Operating Temperature: 0°C - 55°C (32°F - 131°F)
- Storage Temperature: -20°C - 75°C (-4°F - 167°F)
- Humidity: 0~90% RH (non-condensing)
- Power Requirements: 5V
- Colour: Black

Miscellaneous:

- Packaging Type: Carton box
- Packaging Dimensions: 235x63x198mm (9.25x2.48x7.8in)
- Gross Weight: 0.860kg (1.89lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents:

- 2 Port Dual Head DisplayPort 1.2 KVM Switch
- IR Remote Control with CR2025 Battery
- 5VDC 4A Multi-country power supply (UK, EU, US, AUS adapters)
- Lindy Manual

Purchasing Information:

- No.: 39306
- EAN: 4002888393065