



Delock Adapter HDMI male > DVI / VGA / Displayport female 4K black

Description

With this HDMI adapter by Delock, the system can be extended by a VGA, Displayport or DVI interface and various devices such as TV, beamer, monitor etc. can be connected. Only one monitor can be used on the adapter.



Specification

- Connectors:
 - 1 x HDMI-A 19 pin male
 - 1 x USB 2.0 Type-A male (power supply) >
 - 1 x VGA 15 pin female
 - 1 x Displayport 20 pin female
 - 1 x DVI 24+5 female with nuts
- Chipset: PS8222, STDP2600, AG6200
- Displayport 1.2 and High Speed HDMI with Ethernet (HEC) specification
- DVI-D (Single Link), VGA not wired
- Only 1 monitor usable with the adapter
- Audio signal is transmitted only over Displayport
- Displayport specification:
 - Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
 - Supports HDCP 1.4
- VGA / DVI specification:
 - Resolution up to 1920 x 1080 @ 60 Hz (depending on the system and the connected hardware)
- Cable length without connectors: ca. 13.5 cm
- Colour: black
- OS independent, no driver installation necessary

System requirements

- A free HDMI-A female
- A free USB Type-A female port

Package content

- HDMI to DVI / VGA / Displayport Adapter

Item no. 62959


EAN: 4043619629596

Country of origin: China

Package: Retail Box



Images





General	
Specification:	standard Displayport 1.2 High Speed HDMI with Ethernet HDCP 1.4
Supported operating system:	standard OS independent, no driver installation necessary
Interface	
Output:	standard 1 x DVI-I 24+5 female 1 x Displayport 20 pin female 1 x VGA 15 pin female
Input:	standard 1 x HDMI-A 19 pin male 1 x USB 2.0 Type-A male
Technical characteristics	
Chipset:	standard Parade PS8222 AG6200 STDP2600
Maximum screen resolution:	standard 3840 x 2160 @ 30 Hz 1920 x 1080 @ 60 Hz
Signal transmission:	standard video audio
Physical characteristics	
Cable length:	standard 13.5 cm
Colour:	standard black