

Specifications

Model			QM43C	QM50C	QM55C	QM65C	QM75C	QM85C
Display Panel	Diagonal Size	Class	43	50	55	65	75	85
		Measured	42.5	48.5	54.6	64.5	74.5	84.5
	Resolution		3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)
	Brightness (Typ.)		500 nit	500 nit	500 nit	500 nit	500 nit	500 nit
	Orientation		Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
	Haze		25%	25%	25%	25%	25%	25%
	Contrast Ratio (Typ.)		4,000:1 (* IPS - 1,200:1)	4,000:1 (* IPS - 1,200:1)	4,000:1	4,000:1	4,000:1	4,000:1
	Type		VA/IPS	VA/IPS	VA	VA	VA	VA
	Active Display Area		941.184 (H) x 529.416 (V)	1,095.84 (H) x 616.4 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.5 2(V)	1,650.24 (H) x 928.26 (V)	1,872.0 (H) x 1,053.01 (V)
	Pixel Pitch (mm)		0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429	0.487 x 0.487
Color Gamut		NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	
Operation Hour		24/7	24/7	24/7	24/7	24/7	24/7	
Connectivity / Sound	Input	Video	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)
		Audio	N/A	N/A	N/A	N/A	N/A	N/A
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		Tuner	N/A	N/A	N/A	N/A	N/A	N/A
		Video	N/A	N/A	N/A	N/A	N/A	N/A
	Output	Audio	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
		USB	N/A	N/A	N/A	N/A	N/A	N/A
		WiFi / BT	O/O	O/O	O/O	O/O	O/O	O/O
	External Control		RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45
	Speaker		10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch
Mechanical Spec	Dimension (mm)	Set	969.5 x 557.8 x 28.5	1,124.1 x 644.8 x 28.5	1,237.9 x 708.8 x 28.5	1,456.8 x 831.9 x 28.5	1,682.3 x 960.4 x 28.5	1,904.3 x 1,085.3 x 28.5
		Package	TBD	TBD	TBD	TBD	TBD	TBD
	Weight (kg)	Set	TBD	TBD	TBD	TBD	TBD	TBD
		Package	TBD	TBD	TBD	TBD	TBD	TBD
	VESA Mount		200 x 200	200 x 200	200 x 200	400 x 300	400 x 400	400 x 400
	VESA Mount Screw (Min-Max)		M8, 12-14mm	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm
Bezel Width (mm)		11.5 (Even)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)	13.9 (Even)	
Features	Key		UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0
	Internal Player	Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0
		Processor	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core
	Storage (FDM)	Capacity	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)
		Cache	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR
	H/W	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor
		Ambient Sensor	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level
	Special	Wi-Fi	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT
		Signage New Home Workspace	(Microsoft371/VMWare/RDP) Custom Home Auto Source	(Microsoft371/VMWare/RDP) Custom Home Auto Source	(Microsoft371/VMWare/RDP) Custom Home Auto Source	(Microsoft371/VMWare/RDP) Custom Home Auto Source	(Microsoft371/VMWare/RDP) Custom Home Auto Source	(Microsoft371/VMWare/RDP) Custom Home Auto Source
	S/W	Switching & Recovery	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode
Dicom Simulation Mode		SmartView+	SmartView+	SmartView+	SmartView+	SmartView+	SmartView+	
Upgradable Web-Engine		Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	
Video Conference Solution		Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	
Certification	Safety		60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1
	EMC		Class B	Class B	Class B	Class B	Class B	Class A
	Environment		ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT
	IP Rating		IP5x	IP5x	IP5x	IP5x	IP5x	IP5x
	Security		802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP
	Power Supply		AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz
Power	Power Consumption	Max[W/h]	TBD	TBD	TBD	TBD	TBD	
		Typical[W/h]	TBD	TBD	TBD	TBD	TBD	
	Sleep mode	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	
Operating Condition	Temperature		0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	
	Relative Humidity		10-80%	10-80%	10-80%	10-80%	10-80%	
Accessories	Included		Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries	Quick Setup Guide, Warranty Card, Power Cord, RS232C (In) Gender Remote Controller & Batteries
	Optional	Stand	WMN-L4355C	WMN-L4355C	WMN-L4355C	WMN-L4355C	WMN-L4355C	N/A
		Mount	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	N/A
	Specialty		TBD	TBD	TBD	TBD	TBD	TBD

* This specification is not a finalized version, so some specifications may change at the end of June.

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

2023-06

SAMSUNG



Crystal UHD Signage

QMC series

Slim design. Stunning performance.

Introducing the QMC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features



Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.



Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.



Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.



Smartview+

In the QMC series, SmartView+ enables wireless screen sharing for easy collaboration and quick screen switching with just a click.



Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.



Energy star / EPEAT Bronze / TÜV Rheinland Carbon Footprint

Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.