

# RDX® QuikStor®

DATA SHEET

## Rugged, Reliable, Removable Storage for your Business

The Overland-Tandberg RDX QuikStor is an established standard, with attributes beyond other simple data storage products. RDX is the trusted removable disk technology. The tough, armored design provides a reliable and valuable data repository. On the go capability makes it ideal for off-site disconnected storage for disaster recovery. Your Lifeline for all your business data.



### Enterprise Reliability

The exploding growth of mission-critical digital content combined with government-regulated retention policies has created a need for secure, reliable and portable data protection solutions at an affordable cost. The Overland-Tandberg RDX QuikStor technology delivers a rugged design for maximum data protection and secure handling. Full backward/forward compatibility allows users to scale to higher capacities, without worrying about QuikStor generations.

### High Performance

SuperSpeed USB 3.0 and SATA III interfaces offer high performance. With a choice of hard disk and solid-state disk media, unique performance requirements are met. From professional workstations to the low-end enterprise, RDX QuikStor provides users with best-in-class backup and archive capability that is ideally suited to help users get their businesses up and running quickly in the event of data loss.

### External USB3+ Version for more Mobility

The external RDX USB3+ QuikStor system is USB powered. It is as easy to use as an external USB disk drive but much more robust and reliable. With more convenience for the traditional backup tasks it enables RDX for outdoor usage like scientific data collection, in the media and entertainment environment, mobile workforce or just for easy data distribution across locations.

### Fixed Disk Mode for Windows® Backup

RDX QuikStor provides a fixed disk mode in USB 3.0 systems and is the only removable storage device that integrates seamlessly into Windows-backup utility. Users don't have to install additional software for data protection on Windows.

### Capacity Expansion and Media Rotation

For best practice, multiple media should be used for backup and stored off-site for disaster recovery purposes. Media Spanning to multiple RDX media is possible with supported backup software and allows backups to grow and to expand capacity beyond a single RDX media.

### Additional Protection

Overland-Tandberg offers enhanced security features for RDX to satisfy the requirements of a broad area of applications. **RDX WORM** enhances RDX for compliant archiving (optional software solution). **RDX RansomBlock** protects backup data stored on RDX media against virus and ransomware attacks. **PowerEncrypt** hardware encryption for SATA III systems and RDX Cartridge Encryptor (RCE) software for USB systems are features to encrypt data stored on RDX media at no extra cost.

#### Key benefits

- **Fast Access**  
Disk-based speed and data access.
- **Budget-Friendly**  
Cost-effective solution that suits all sectors from SOHO users to departmental users.
- **Flexible**  
USB 3.0 SuperSpeed and SATA III interface, internal and external systems and HDD media in different capacities.
- **Rugged and Tough**  
Shock and drop protected media design ensures durability and reliability with more than 10 years archive life. Vibration isolation ensures read/write performance reliability.
- **Removable & Secure**  
Expand capacity and span backups across media. Media rotation and off-site copies for archiving and peace of mind.
- **Compliant & Secure**  
Use rdxLOCK software for WORM compliant archive and ransomware protection.
- **Encryption**  
The RDX SATA III systems provide FIPS 140-2 validated hardware encryption.
- **Mobile**  
The external USB3+ version is USB powered and can be used as a mobile storage device.
- **19" Rack Integration with QuadPAK™**  
Easy installation of up to 4 external RDX USB systems.
- **Windows Backup Support**  
Configurable operating mode for Windows Backup Application in all USB 3.0 versions.



Specifications	Internal RDX Systems		External RDX Systems
Form Factor	3.5" (SATA III/USB 3.0)	5.25" (SATA III/USB 3.0)	External Housing (USB 3.0)
Height	41 mm (1.63 in)	41 mm (1.63 in)	52 mm (2.04 in)
Width	102 mm (4.00 in)	146mm (5.78 in)	110 mm (4.32 in)
Length	159 mm (6.28 in) incl. bezel	170.72 mm (6.72 in) incl. bezel	178 mm (7.00 in) incl. bezel
Weight	408 g (0.9 lb)	635 g (1.4 lb)	615 g (1.35 lb)
Mounting & Operating Orientation	Horizontal or Vertical		
Interface	SATA III	USB 3.0	USB 3.0 (USB powered)
Interface Connector	SATA	Type-B	Type-B
Interface Operation Mode	Removable disk	Removable disk & Fixed disk	Removable disk & Fixed disk
Transfer Rate Average Sustained (media dependent)	Up to 330 MB/s*	Up to 260 MB/s*	Up to 260 MB/s*
Power Specifications	SATA III	USB 3.0	USB 3.0 (USB powered)
Voltage	+5 V	+5 V      +12 V	+5 V
Current at Read/Write (Typical / Peak)	0.9 A / 1.6 A	0.9 A / 1.6 A      0.005 mA / 1.4 A	0.9 A / 1.6 A
Power Connector	SATA Power	4-Pin Molex	optional: 5.5 mm
Power Adapter	4-Pin Molex to SATA Power	SATA Power to 4-Pin Molex	optional power adapter: +5 V (+/- 10%) 2,4 A to +12 V (+/- 10%) 1,0 A
Media	500GB, 1TB, 2TB, 3TB, 4TB or 5TB <i>See RDX Media data sheet for more information</i>		
Read/Write Compatibility	Forward/backward compatibility to all RDX systems		
Reliability	1m drop to tile over concrete floor (Media)		
Media Drop Shock (Non-operating)	System: 10,000 insertion / removal cycles, Media: 5,000 insertion / removal cycles		
Load / Unload (Minimum)	550,000 Hours		
MTBF	0.5G (operating), 1.0G (non-operating)		
Vibration (max)			
Environmental			
Temperature	+10°C to +40°C (+50°F to +104°F) (operating), -40°C to +65°C (-40°F to +149°F) (non-operating)		
Relative Humidity	20% – 80% (non-condensing, operating), 8% – 90% (non-condensing, non-operating)		
Altitude	-15 m to 3,048 m (-50 ft to 10,000 ft) (operating), -15 m to 10,660 m (-50 ft to 35,000 ft) (non-operating)		
Other Features			
Encryption	PowerEncrypt - hardware-based encryption for SATA III internal systems, FIPS 140-2 validated. (Software encryption is supported on all QuikStor systems.)		
WORM	Enables compliant archiving with rdxLOCK Software, KPMG certified (optional)		
RansomBlock	Protects against virus and ransomware attacks with rdxLOCK Software (optional)		
Compression and Deduplication	Supports software-based compression and deduplication		
Windows Backup	Fixed Disk Mode for Windows Backup Utility available in all USB 3.0 versions		
Accessories			
RDX® TENCASE	Optional, stores up to 10 RDX media in a robust and secure box (part. no. 1022291)		
RDX® QuadPAK™	Optional, allows up to 4 RDX external QuikStor systems to be securely installed in a 19" rack (part. no. 3800-RAK)		
FIPS 140-2 Security Label Set	Optional, needed for validation of tamper evident for FIPS 140-2 (part. no. 1022445)		

\* Depending on media type

Sales and support for Overland-Tandberg products and solutions are available in over 90 countries.  
Contact us today at [salesemea@overlandtandberg.com](mailto:salesemea@overlandtandberg.com)

DS\_v7\_dec06\_2019

©2019 Overland-Tandberg. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Overland-Tandberg shall not be liable for technical or editorial errors or omissions contained herein.