

## GX20 Data Sheet

# Meraki Go Security Gateway



## GX20

### Performance

---

- Firewall Throughput - 250 Mbp/s
- Recommended for 50 clients or fewer

### Network and Security Services

---

- Stateful firewall
- Port Forwarding
- DHCP services
- DNS based security powered by Cisco Umbrella (additional subscription required)

### Power

---

- 50W (54V / 0.92 A) Power Supply Included

### Interfaces

---

- WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)
- LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)
- PoE: 1x 802.3af enabled port (15.5W)

### Environment

---

- Operating temperature: 32 °F to 104 °F (0 °C to 40 °C)
- Humidity: 5 to 95% non-condensing
- Kensington lock hard point

### LED Indicators

---

- 2 Ethernet status

- 1 power/booting/firmware upgrade status

## Physical Dimensions

---

- 6.83" x 4.41" x 1.04" (173.4mm x 112mm x 26.3mm), not including deskmount feet or mount plate

## In the Box

---

- GX20-HW: Meraki Go Security Gateway
- Wall mount and screw kit
- Quick start guide
- PSU and ethernet cable

## Warranty

---

- 1 year hardware warranty

## Model List / Accessories

---

GX20-HW-XX Security Gateway - Desktop

GA-PWR-50WAC 50W Replacement Laptop Style Adapter for GX20

XX = US/UK/EU

Cisco Systems, Inc. | 500 Terry A. Francois Blvd, San Francisco, CA 94158 | (415) 432-1000 | [help@meraki-go.com](mailto:help@meraki-go.com)