

Vero B7-Serie

Vero B277UGbemiqpruzx

Environmentally friendly in everyday business

The Vero B7 series impresses with a unique design paired with all the features that a modern business monitor must have. The ZeroFrame design convinces all along the line and enables a seamless multi-monitor setup without disturbing frames. Thanks to the flexibly adjustable ErgoStand, the monitors of the B7 series can be adjusted in height and rotated by 90° (pivot function) - all in the name of ergonomics. This series is ENERGY STAR®, TCO and EPEAT certified, reflecting Acer's commitment to environmental protection. It is made of up to 85% post-consumer recycled (PCR) plastic, up to 5% OBP (Ocean Bound Plastic) and uses 100% recyclable packaging.



- Diagonal size: 68.6 cm (27.0 inches)
- Response time: 4ms(GTG)
- Brightness: 350 cd/m²
- Signal input: 1x HDMI, 1xDP(1.2) + 1xDPOut, 1x Type-C (90W), 4x USB 3.2 (1up 4down), Audio Out, 1x RJ45











Vero B277UGbemiqpruzx

SPECIFICATIONS







Technical Specifications

Backlight type

VGA

DVI

Off mode Power

68.6 cm (27.0 inches) Diagonal size 597x336 mm Active display area (WxH) Aspect ratio 16:9 Resolution 2560x1440 IPS Technology Panel type Response time 4ms(GTG) 350 cd/m² Brightness

Acer CrystalBrite No, anti-reflective display Viewing angle (h/v) CR>10:1 178/178°

Static contrast ratio 1000:1 Dynamic contrast ratio 100M:1 16.7M Colors Colour space 99% sRGB 2 x 2 watts Speaker

Signal input 1x HDMI, 1xDP(1.2) + 1xDPOut, 1x Type-C

LED

(90W), 4x USB 3.2 (1up 4down), Audio Out, 1x

0,3 W

USB Type-C 1x Type-C (90W) Black

Chassis colour

Frequency (H/V) HDMI:31~177.6KHz / 48~120Hz, DP:31~177.6KHz / 48~120Hz

Refresh rate (max.) 1x (HDMI 2.0) DisplayPort 1xDP(1.2) + 1xDPOut

USB 3.1 Type-C 1x Type-C (90W) 4x USB 3.2 (1up 4down) USB Hub

Additional ports 1x RJ45

Power supply and consumption

Power supply Internal EPREL No. tbd **Energy Efficiency Class** On-mode Power 21 kWh/1000h Standby mode Power 0,5 W

Tilt angle -5°~35° +/-60° Swivel angle 165 mm Height adjust range Pivot function +/-90° VESA wall mounting 100x100 mm

Norms and Standards

Warranty 36 months Carry In

Certification TCO Edge, Win 10 compliant, EnergyStar

FPFAT FPFAT Gold 30 000 hrs. at 25°C MTRE

Dimensions and weight

Dimension w/o stand (W \times H \times D)

Weight (unpacked) 5,65 kg Package Dimensions 69.40x51.40x14 Weight (packed) 9,33 kg Weight w/o stand 3,49 kg

48 Pcs (128x114x219.60 cm) Pallet qty and size ($H \times W \times D$)

Container qty (20'/40') 576 / 1,224

Others

EN, DE, ES, NL, FR, IT, FI, RU, P, CN, PL OSD languages

Operating ambient temperature 5°C bis 35°C Operating ambient humidity 10% bis 85% Storage ambient temperature -20°C to 60°C Kensington Security Slot Yes

Ordering Information

Model Vero B277UGbemiqpruzx Product line Part number UM.HB7EE.G21 FAN 4711474360885

Special features

Special features Acer VisionCare Yes KVM Switch Yes Acer Display Widget Yes

HDR Support HDR Ready (HDR 10)

This data sheet is subject to change without notice. Availability may vary from region to region. Acer is not liable for any errors or omissions contained in the product descriptions. In addition to the standard warranty conditions, the statutory warranty regulations also apply to consumers. For more information on exclusions and limitations, please refer to our warranty conditions for the respective product. If the warranty period in the PDF document for the warranty conditions differs from the information on the Acer homepage, the information given on this website applies and not the information contained in the PDF. Copyright 2024 Acer, Inc. all rights reserved. Acer and the Acer logo are registered trademarks of Acer Incorporated. All other trademarks, registered trademarks and/or service marks mentioned or otherwise recognizable are the property of their respective owners. All prices quoted are manufacturer's suggested retail prices.