




### Key Features

- Write Away quick-start annotation, enhanced by 50-point touch and palm rejection for precise writing.
- 70W total output power speaker system with built-in 8-microphone array, for rich, immersive audio.
- EDLA-Certified with Android 14, integrated ViewSonic Education Software for seamless functionality.
- NFC and SSO sign-in for swift access to the intuitive launcher and personal settings.
- EPEAT Silver certified for enhanced energy efficiency and sustainability.



### Product Description

Bring energy-efficient performance to your classroom with the ViewBoard® IFP51 Series, available in sizes from 55" to 98" to suit any setup. Seamless interactivity is at your fingertips, thanks to its ultra-responsive 50-point touch technology and instant 'write away' annotation. Powered by Android 14 and EDLA-Certified, it offers secure access to Google Play apps, while NFC and SSO sign-in ensure instant access to personalized settings. Integrated ViewSonic Education Software completes the experience with tools for whiteboarding, casting, and device management—delivering a more dynamic and efficient teaching experience.



Visit Us [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Panel Size:	75"
Panel Type:	TFT LCD Module with DLED Backlight.
Display Area (mm):	1650.24mm(H) x 928.26mm(V) (74.5")
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160
Colors:	1.07G colors
Brightness:	500 nits
Contrast Ratio:	1200:1 (typ.) / 5000:1 (DCR)
Response Time:	6.5 ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	50,000 Hours (Min)
Surface Treatment:	Hardness:9H, Anti-Glare+Anti-Fingerprint, 3.2mm thickness, tempered laminated glass
Orientation:	Landscape

**PLATFORM**

Processor:	Octa-Core CPU
RAM:	16GB
Storage:	128GB

**TOUCH**

Type/ Tech:	Ultra Fine Touch Technology (IR Recognition)
Touch Resolution:	32767 x 32767
Touch Point:	EDLA/Android/Windows: 50 points of touch; all other channels: 20 points.
Palm Rejection:	Yes
CG +OC bonding:	Zero bonding

**INPUT**

HDMI:	x4 (Frontx2:HDMI2.1 with CEC, HDCP ; Rearx2: [(HDMI2.1 with CEC, HDCP)x1+(HDMI2.1 with CEC, HDCP, ARC)x1]
RGB / VGA:	x1
DisplayPort:	x1
Audio:	x1
RS232:	x1
SD/SDHC:	TF Card Slot(Micro SD)
OPS:	x1 PC Slot
Wifi slot:	x1

**OUTPUT**

HDMI:	x1 (HDMI 2.1, HDCP 1.x)
Audio:	x1 (Line out)
SPDIF:	x1 (optical)

**LAN**

RJ45:	x2
-------	----

**USB**

Type A:	x5 (Front x2 and Rear x 2 with USB3.2 Gen 1, all support SmartPort USB ; Rear x 1 with USB 2.0 for system update)
Type B:	x2 (Front x 1 and Rear x 1 with USB3.2 Gen 1)
Type C:	x3 (Frontx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, PD 65W; Rearx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, PD 15W; Topx1 with USB3.2 Gen 1, PD 15W)

**SPEAKERS**

25W x 2 front soundbar + 20W x 1 subwoofer

**MICROPHONE**

Built-in 8-array microphone

**TOP CAMERA PLATE**

Yes

**COMPATIBILITY**

RGB PC/HDMI PC:	1920x1080 @ 60Hz
HDMI:	3840x2160
DisplayPort:	3840x2160

**EMBEDDED OS**

EDLA-certified with Android 14

**BUNDLED SOFTWARE**

Basic Annotation Software:	myViewBoard for Android
Pro Annotation Software:	myViewBoard for Windows (embedded in VPC)
Wireless Presentation:	AirSync
Device Management:	Manager
ViewSonic Launcher:	Yes

**SPECIAL FEATURES**

All-in-one USB port:	USB 3.2 Gen 1 "SmartPort USB" to all channels
Simple LAN sharing between IFP and slot-in device:	10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000)
Light Sensor:	Yes
NFC Reader:	Yes
Pen Sensor:	Yes
OTA updates:	Yes

**POWER**

Voltage:	100-240V AC +/- 10% Wide Range
Consumption:	On: 99.84W ; Off: < 0.5 W

**ERGONOMICS**

Wall Mount (VESA®):	800 x 400
---------------------	-----------

**OPERATING CONDITIONS**

Temperature (° C):	0°C to 40°C
Humidity:	20% ~ 80% RH non-condensing

**DIMENSIONS (W X H X D)**

Physical (inch / mm):	67.29 x 40.85 x 3.36 in / 1709.1 x 1037.5 x 85.5 mm
Packaging (inch / mm):	73.35 x 45.79 x 8.86 in / 1863 x 1163 x 225 mm

**WEIGHT**

Net (lb / kg):	101.54 lb / 46.06 kg
Gross (lb / kg):	126.88 lb / 57.55 kg

**REGULATIONS**

cTUVus, FCC ID/IC ID, FCC SDoC, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT Silver, UK-EEL, BSMI, BIS, LBL ( Low Blue Light Certification), Flicker Free, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH , Packing waste, CA65, PAIA

**PACKAGE CONTENTS**

- Power Cord x1 3 meters,
- USB Type-C cable x1 1.8 meters, USB-IF certified
- USB Touch cable x1 3 meters
- Touch pen (Passive pen) x 2
- Quick Start Guide
- RS232 adapter x1
- Clamp x 5
- Camera Plate x1
- Screw x 8 (camera 2+2, wall mount 4)
- HDMI cable x1 3meters (HDMI LA certified)
- Remote controller x1
- AAA battery x2
- Compliance statement

**COMPATIBLE SLOT-IN PC**

VPCF5-W33-G1,  
VPC37-W53-G1,  
VPC35-W53-G1,  
VPC-A31-O1

**COMPATIBLE ACCESSORIES**

VB-WIFI-001:	802.11 a/b/g/n/ac/ax; Bluetooth: Support 2.1/3.0/4.0/5.2 BLE
VB-WMK-001-2C:	Up to 900 x 600 mm; Screw Type: M5, M6, M8; Support Panel Size: 55"-98"; Installation Standard: VESA

**LANGUAGE SUPPORT FOR MYVIEWBOARD**

Arabic, Bangla, Basque, Catalan, Chinese (Traditional), Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Kannada, Kazakh, Latvian, Lithuanian, Malaysian, Marathi, Polish, Portuguese, Punjabi, Romanian, Russian, Slovakian, Slovenian, Spanish, Swedish, Tamil, Telugu, Thai, Turkish, Ukrainian, Vietnamese