



Adventurer 5M Pro

Fast and User-friendly



Adventurer 5M Pro is well-suited for beginners, individual users, families, and educational institutions. Just one-click printing, without complicated operation procedures. Realize your ideas effortlessly.



Full-auto one-click leveling



Maximum speed 600mm/s




Core XY structure



3-second quick-swap nozzle



Dual air filtration system





50dB silent printing



Full-auto one-click leveling, flawless first layer

Adventurer 5M Pro features a full-auto one-click leveling system. It measures the distance and then calculates the correct offsets. No tools, no manual Z-axis calibration, while ensuring perfect first layer.





10 Minutes

From unboxing to starting printing



Efficiency and quality combined



10 minutes

From unboxing to starting printing



Printing

Maximum speed **600mm/s**

Maximum acceleration **20000mm/s²**



Less waiting time

Nozzle with a flow of **32mm³/s**

50w heating power

200°C heating up in **35 seconds**

Astronaut

104*118*200mm (228g)


Adventurer 5M Pro

4h10min








Others

19h20min



Robust designs for superior quality






Eco-friendly printing

Adventurer 5M Pro adopts a dual filtration system of internal and external circulation. Dual-layer filtration: HEPA13 and activated carbon, effectively blocking 99% of particles and VOCs, thus protecting your respiratory system.



Internal Circulation Filtration

Continuously filters and circulates the air inside the chamber.
(Suitable for ABS, etc.)



External Circulation Filtration

Draws fresh air from the outside into the chamber while the filtered internal air circulates outside the printer.
(Suitable for PLA/PETG, etc.)




50dB low-noise printing,
no disturbance to work
or study




Easy-maintenance nozzle for both rookies and experts

Quick-detachable nozzle requires no tools for change in **just 3 seconds**

Various nozzle diameter (0.25/0.4/0.6/0.8mm) options suitable for both high-precision and high-efficiency mode



Remote Camera Monitoring



Filament Run-out Reminder




Automatic Shutdown



Power Loss Recovery



Flexible PEI Steel Plate



Integrated Printing Management



Adventurer 5M Pro

Enclosed 3D printer equipped with a dual filtration system, suitable for use in closed environments such as study rooms and classrooms

Parameters

Machine Name	Adventurer 5M Pro
Extruder	Direct drive; Qty: 1
Filament	*PLA/*PETG/*TPU (0.4mm nozzle) ABS/ASA PLA-CF/PETG-CF (0.6/0.8mm nozzle) <small>Note: Materials marked with * are recommended for printing.</small>
Nozzle Diameter	0.4mm/0.6mm/0.8mm/0.25mm
Extruder Temperature	280°C
Platform Temperature	110°C
Build Volume	220*220*220mm
Speed	Max traveling speed: 600mm/s
Acceleration	Max acceleration: 20000mm/s ²
Build Plate	Flexible removable PEI steel plate
Display Screen	4.3-inch
Device Size	380*400*453mm (excluding the spool holder)
Power Supply	AC 100~240V, 50/60Hz, 350W
Compatible Slicing Software	FlashPrint/Prusa Slicer/Cura/Orca Slicer
Air Filtration	Internal circulation + external circulation (HEPA 13 + activated carbon)
Shell	Enclosed
Noise	Low-noise mode: 50dB; Standard mode: 55dB
Connectivity	Wi-Fi; Ethernet; USB
Other Functions	Camera monitoring; Filament run-out reminder; Automatic shutdown; Power loss recovery



Zhejiang Flashforge 3D Technology Co., Ltd.

Address: No.518 XianYuan Road, Jinhua City, Zhejiang Province, China

Service Hotline: +86 579 82273989

Email: support@flashforge.com



Follow us