

## OVERVIEW

The Vertiv™ Geist™ Basic Rack PDU delivers reliable power distribution at a competitive price point. The Basic PDU is the entry-level solution in the Vertiv Geist Rack PDU family, providing basic, reliable power distribution in all IT environments.

### Benefits

- Reliable power distribution at a low cost point
- Every unit is tested for reliability and functionality — no batch tests
- Fast, inexpensive customization, including non-standard cord lengths
- Standard three-year warranty, upgraded to five years with early product registration

### Part Number:

VP7553 Basic, Standard

### Power Configuration:

32A, 230V, 7.3kW

### Physical Configuration:

66in / 1683mm Vertical

### Product Summary:

VP7553 — Basic, Standard, 32A, 230V, Vertical, (20) IEC C13, (4) IEC C19, breakerless, 3m power cord with 2P+E (IP44), Black Powder Coat.

## Specifications and Options

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	230V
<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	7.3kW
<b>Frequency</b>	50/60 Hz
<b>Over Current Protection</b>	(2) 16A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Wire Gauge</b>	4mm² H07RN-F
<b>Power Cable Length</b>	3m
<b>Plug Type</b>	IEC60309 2P + E, 32A, 250V, Splashproof IP44
<b>Combined Total Receptacle/Socket Quantity</b>	24
<b>Receptacle/Socket Type #1</b>	IEC C13
- Quantity on Face	20
- Quantity per Breaker	10
- Style	Banks of 2
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
<b>Receptacle/Socket Type #2</b>	IEC C19
- Quantity on Face	4
- Quantity per Breaker	2
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
<b>Continuous Operating Temperature Range</b>	10-45C / 50-113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	66in / 1683mm Vertical Rackmount
<b>7938 Vertical Mounting Bracket Kit</b>	Yes

## Specifications and Options (cont'd)

<b>Toolless Mounting Hardware — Center to Center Spacing</b>	1556mm and 1645mm
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55024
<b>Certification/Agency Approvals</b>	Complies with IEC 60950-1 (CB Certificate Available)
<b>Certification/Agency Approvals</b>	CE Marked
<b>Chassis Dimensions (HxWxD)</b>	1683mm x 51mm x 51mm
<b>Doghouse (D)</b>	37mm

