

# Rittal – The System.

Faster – better – everywhere.

## ► CMC III power pack for PU, PU Compact, LED light strip, door control module – DK 7030.060

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CMC III power pack for PU, PU Compact, LED light strip, door control module – DK 7030.060

created: 12.07.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	The power pack is specifically tailored to the CMC III design and may be positioned in a mounting unit. As well as a special connector for the CMC III Processing Unit/Compact, there are also two further terminals available as 24 V outputs.
<b>Material:</b>	Plastic
<b>Surface finish:</b>	Front: Smooth Enclosure: Textured
<b>Colour:</b>	Front: RAL 9005 Enclosure: RAL 7035
<b>Supply includes:</b>	Connection cable 24 V (DC) Assembly parts for mounting on surfaces

## Product description

<b>To fit:</b>	Enclosure type: PU Enclosure type: PU Compact Enclosure type: LED light strip Enclosure type: Door control module
<b>Suitable for CMC components:</b>	CMC III Processing Unit CMC III Processing Unit Compact CMC III CAN bus interface for two CMC II unit components
<b>Dimensions:</b>	Width: 138 mm Height: 40 mm Depth: 132 mm

<b>Rated operating voltage:</b>	100 V - 240 V, 50 Hz/60 Hz
<b>Installation dimensions:</b>	Installation depth: 120 mm Build depth: 12 mm
<b>Operating temperature:</b>	Operation (environment): +0 °C...+40 °C
<b>Ambient humidity (non-condensing):</b>	Operation (environment): 5 % - 95 %
<b>Power pack:</b>	Output voltage: 24 V DC
<b>Output current (max.):</b>	2.5 A
<b>Connections:</b>	Input: IEC 320 connector C14
<b>Equipment (electrical):</b>	Length of connection cable: 600 mm
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	0.65 kg
<b>Copper weight (kg per piece):</b>	0
<b>EAN:</b>	4028177659384
<b>Customs tariff number:</b>	85043121
<b>ETIM 7.0:</b>	EC002627
<b>ETIM 6.0:</b>	EC002627
<b>eCl@ss 8.0/8.1:</b>	27189253
<b>eCl@ss 6.0/6.1:</b>	27189253
<b>Product description:</b>	DK CMC III Power pack, For power supply of the CMC III Processing Units, Input: C14 100-230 V, 50/60 Hz, Output: 24 V DC, 2 A
<b>Approvals</b>	
<b>Approvals:</b>	UL
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity FCC

