



Delock External Industry Hub 7 x USB 3.0 Type-A with 15 kV ESD protection

Description

This solid industry capable USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by seven USB Type-A connectors, which supports the USB Battery Charging specification BC1.2. Thus, connected devices such as smartphones can be charged faster. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



Specification

- Connectors:
 - 1 x USB 3.0 Type-B female >
 - 7 x USB 3.0 Type-A female - Battery Charging specification BC1.2
 - 1 x 9 - 40 V DC jack
 - 1 x 3 pin terminal power connector
- Chipset: VIA VL811+
- Data transfer rate up to:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- 8 x LED indicator
- USB ports with screw holes
- Robust metal housing
- Removable wallmount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 40 V
- Automatic detection of the input polarity of the power connectors
- ESD protection up to 15 kV for all ports
- Dimensions (LxWxH): ca. 158 x 80 x 32 mm
- Colour: black
- Plug & Play

Power supply specification

- 9 - 40 V
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 3.16.x, ex Mac OS 10.9
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail

Item no. 63311

EAN: 4043619633111


Country of origin: China

Package: Retail Box



- 1 x 3 pin terminal block
- User manual

Images



**General**

Function: Battery Charging BC1.2
Plug & Play

Mounting type: DIN rail
Screw mounting

Supported operating system: Linux Kernel 3.16 or above
Mac OS 10.9 or above
Windows 7 32-bit
Windows 7 64-bit
Windows 8.1 32-bit
Windows 8.1 64-bit
Windows 10 32-bit

LED indicator: 8 x

Interface

Connector 1: 1 x USB 3.0 Type-B female

Connector 2: 7 x USB 3.0 Type-A female - Battery Charging specification BC1.2

connector 3: 1 x 9 – 40 V DC jack

connector 4: 1 x 3 pin terminal power connector

Physical characteristics

Length: 158 mm

Width: 80 mm

Height: 32 mm

Colour: black