Technical Specifications

HP E14 G4 Portable Monitor



Left

- 1. OSD control buttons
- 2. USB Type C® Port

Technical Specifications

HP E14 G4 Portable Monitor



Right

- 1. Power button
- 2. USB Type C® Port

Technical Specifications

Models: 1B065A8/1B065AA

Panel Specifications Display Size (Diagonal) 14-in

Panel Technology **IPS Refresh Rate** 60Hz **Panel Bit Depth** 8-bit **Aspect Ratio** 16:9 **Brightness (Typical)** 400 cd/m² **Contrast Ratio (Static)** 800:1 **Contrast Ratio Minimum (Static)** 600:1 **Dynamic Contrast Ratio** 5,000,000:1

Flicker Free Yes

Pixel Pitch 0.1611 x 0.1611 mm

Pixels Per Inch (PPI) 157

Backlight Lamp Life (to half brightness 15k minimum

- in hours)

Backlight TypeEdge-litScreen TreatmentAnti-glareHardness3H

Haze 24%

Response Time - Typical 5ms GtG (with overdrive)
Horizontal Viewing Angle (typical 160(min); 178(typ)

CR>10)

Vertical Viewing Angle (typical CR>10) 160(min); 178(typ)
Panel Active Area (w x h) 309.31 x 173.99 mm

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage NTSC 72%

Monitor Specifications Bezel 3-sided Micro Edge

ColorSliver StandHeight Adjustment RangeNo height adjust

Warranty 3/3/0

Low Blue Light ModeYes (TÜV certified) **Native Resolution**Full HD (1920 x 1080)

1. Apply to high resolution and/or high frame rate displays only. CONFIRM WITH EPM whether disclaimer applies.

Maximum Resolution1920x1080 60HzPreset Graphic Modes/Supported640 x 480 @ 60HzResolutions720 x 400 @ 70 Hz

800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz

Technical Specifications

1920 x1080 @60Hz

Minimum Vertical Scan Rate 59 Hz **Maximum Vertical Scan Rate** 60 Hz Minimum Horizontal Scan Rate 30.0 kHz **Maximum Horizontal Scan Rate** 80.0 kHz **Maximum Pixel Clock** 140.0 MHz **User Programmable Modes** 10

User-Assignable Function Buttons Yes. 4 buttons **Audio** No Audio

Languages 10 (English, Spanish, German, French, Italian, Netherlands,

Portuguese, Japanese, T-Chinese and S-Chinese)

Connector Types

USB Type-C® Video Input

2 USB Type-C® with DisplayPort® 1.2 Alt mode

Power & Operating Specs

Power Supply

External (From NB PD Power)

Power Source PD Power 5v

Power Consumption - Maximum 6 W **Energy Saving/Standby Mode** 0.3 W **Power Consumption - Typical** 3.5 W **Power Passthrough** up to 65 W

NOTE: requires external power from NB external power supply attached

Operating Conditions

Operating Temperature - Celsius 5 to 35°C Operating Temperature - Fahrenheit 41 to 95°C Non-operating Temperature - Celsius -20° - 60°C Non-operating Temperature -29° - 140°F

Fahrenheit

Operating Humidity 20 – 80% Relative Humidity (non-condensing)

Non-operating Humidity 5 - 95%

Operating Altitude 0 – 5,000 m (16,400 ft.) Non-operating Altitude 0 – 12.192 m (40,000 ft.)

Environmental Features and Certifications

Mercury-free LED display backlighting

Yes, Mercury-free LED backlighting

Arsenic-Free Display Glass Yes Low Halogen Yes

WW application

CE,CB,KC/KCC/NOM/ICES/TUV-GS/ISO 9241-307/

EAC/UL/cTuvs/ISC/CCC/Energy Star 8/ **Agency Approvals and Certifications**

ISC/VCCI/FCC/BSMI/Vietnam MEPS/WEEE /BIS/Cambodia/Taiwan Green mark/UAE

Microsoft WHQL Certification Yes **ENERGY STAR® Certified** Yes **EPEAT®** Registered Yes

Regions need to verify by country SmartWay Transport Partnership -

NA only

Yes (NA sku)

Plastics Recyclable Packaging

(Box, packing materials)

100% fiber packaging, cardboard



Technical Specifications

		<u>Metric</u>	<u>Imperial</u>	
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	32.14 x1.52x 21 cm	12.65X0.60X8.27 in	
•	Product Dimensions (Packed) (W x D x H)	40.50 x 6.10 x 28.40 cm	25.43 x 17.24 x 10.59 in	
	Display Head Dimensions (Unpacked without stand) (W x D x H)	53.94 x 32.33 x 4.85 cm	15.94 x 2.40 x 11.18 in	
	Base Area Footprint (w x d mm)	321.37 x 82 mm	12.65 x 3.23 in	
	Bezel Measurements	Top 5.58mm, side 5.58mm, bottom 29.53mm	Top 0.22, side 0.22, bottom 1.16 in	
	Product Weight (Unpacked with stand)	0.64 kg	1.41 lb	
	Product Weight (Packed)	1.54kg	3.40 lb	
EU Energy Efficiency Class (ERP lot-5)	On-mode Power Consumption	18 W		
	Annual Power Consumption	26 kWh		
	Energy Efficiency Class	В		
	Visible Screen Size	14-inch / 35.56 cm Diagonal		
What's in the box?	Monitor			
	USB Type-C® cable			
	QSP Sleeve			
	Sieeve			
User Guide and Warranty Languages	User Guide Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.		
	Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian		



Turkish.

Portuguese, Russian, Slovenian, Spanish, Swedish and

Summary of Changes

Date of change:	Version History:		Description of change:
February 23, 2021	V1 to V2		Techspecs updated
March 15, 2021	V2 to V3	Added	Power Consumption
	V3 to V4		

Copyright © 2021 HP Development Company, L.P.The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

