

Key **Features**

- Integrated USB-C workstation offers audiovisual and data transfer, and power delivery up to 65W
- USB 3.2 hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort inputs for easy connectivity
- SuperClear® IPS panel with 100Hz variable refresh rate delivers fluid visuals
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



Product **Description**

The ViewSonic VG2409-MHDU-2 is a 24" FHD monitor featuring USB 3.2 Hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort for business and home use. Simplify your work with just one cable that provides audiovisual, data and 65W power transfer. The 100hz variable refresh rate, Eye ProTech technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.







- Menu Control Panel
 Power In
 VESA Compatible(Wall Mount 100 x 100 mm)
 HDMI
 HDMI
 USB Type-C

- 7. USB Type-B Upstream 8. USB Type-A Downstream*2 9. Audio Out 10. Speakers

DISPLAY		ERGONOMICS
Display Size (in.):	24	Height Adjust (mm):
Viewable Area (in.):	23.8	Swivel:
Panel Type:	IPS Technology	Tilt (Forward/Back):
Resolution:	1920 x 1080	Pivot (Right/Left):
Resolution Type:	FHD (Full HD)	WEIGHT (IMPERIAL)
Static Contrast Ratio:	1,300:1 (typ)	Net (lbs):
Dynamic Contrast Ratio:	50M:1	Net Without Stand (lbs)
Light Source:	LED	Gross (lbs):
Brightness:	350 cd/m² (typ)	Net (kg):
Colors:	16.7M	Net Without Stand (kg):
Color Space Support:	8 bit (6 bit + FRC)	Gross (kg):
Aspect Ratio:	16:9	DIMENSIONS (IMPER
Response Time (Typical GTG):	4ms	Packaging (in.):
Response Time (GTG w/OD):	178° horizontal, 178° vertical	Physical (in.):
Viewing Angles:		Physical Without Stand
Backlight Life (Hours): Curvature:	30000 Hrs (Min) Flat	DIMENSIONS (METR
Refresh Rate (Hz):	100	Packaging (mm):
	100	Physical (mm):
Variable Refresh Rate Technology:	Yes	Physical Without Stand
Low Blue Light:	Software solution	GENERAL
Flicker-Free:	Yes	Regulations:
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	
Pixel Size:		PACKAGE CONTENTS:
	0.275 mm (H) x 0.275 mm (V)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Recycle/Disposal:
PC Resolution (max):	1920x1080	
Mac® Resolution (max):	1920x1080	Warranty:
PC Operating System:	Windows 10/11 certified; macOS tested	Power Management:
Mac® Resolution (min):	1920x1080	
CONNECTOR		
USB 3.2 Type A Down Stream:	2	
USB 3.2 Type B Up Stream:	1	
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (65W power charger)	
3.5mm Audio Out:	1	
HDMI 1.4:	1	
DisplayPort:	1	
Power in:	3-pin Socket (IEC C14 / CEE22)	
AUDIO		
Internal Speakers:	2.5Watts x2	
POWER		
Eco Mode (Conserve):	18W	
Eco Mode (optimized):	20W	
Consumption (typical):	22W	
Consumption (max):	24W	
Voltage:	AC 100-240V	
Stand-by:	0.5W	
Power Supply:	Internal Power Supply	
ADDITIONAL HARDWARE		
Kensington Lock Slot:	1	
Cable Organization:	Yes	
CONTROLS		
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)	
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu	
OPERATING CONDITIONS		
Temperature:	32°F to 104°F (0°C to 40°C)	
Humidity (non-condensing):	20% to 90%	
WALL MOUNT		
	100 x 100 mm	
VESA Compatible:		
·	100 x 100 11111	
NPUT SIGNAL	30 ~ 125KHz	
VESA Compatible: NPUT SIGNAL Frequency Horizontal: Frequency Vertical:		

TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C

VIDEO INPUT

Digital Sync:

ERGONOMICS		
Height Adjust (mm):	130	
Swivel:	360°	
Tilt (Forward/Back):	-3.5° / 28°	
Pivot (Right/Left):	90° / 90°	
WEIGHT (IMPERIAL)		
Net (lbs):	12.3	
Net Without Stand (lbs):	7.7	
Gross (lbs):	15.9	
WEIGHT (METRIC)		
Net (kg):	5.6	
Net Without Stand (kg):	3.5	
Gross (kg):	7.2	
DIMENSIONS (IMPERIAL) (WX	(HXD)	
Packaging (in.):	24.5 x 20.5 x 5.7	
Physical (in.):	21.25 x 15.35~20.47 x 9.18	
Physical Without Stand (in.):	21.25 x 12.72 x 2	
DIMENSIONS (METRIC) (WXHXD)		
Packaging (mm):	622 x 520 x 144	
Physical (mm):	539.7 x 389.89~519.89 x 233.29	
Physical Without Stand (mm):	539.7 x 323.18 x 50.9	
GENERAL		
Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO	
PACKAGE CONTENTS:	VG2409-MHDU-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1	
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.	
Warranty:	*Warranty offered may differ from market to market	
Power Management:	Energy Star standards, EPEAT	