

FRITZ!DECT 301

Technical Specifications

Highlights at a glance

- Smart radiator control for the home network
- Manages the room temperature automatically and precisely
- Helps save energy and reduces heating costs by up to 30 percent
- Control with PC, notebook, FRITZ!Fon, smartphone or tablet – even remotely over the Internet and the MyFRITZ!App
- E-paper display for good legibility
- Secure integration in the home network via DECT ULE
- Learns through automatic updates



Technical Specifications

Features

- Weekly schedule with up to 8 switching points a day
- Setting wheel for changing the room temperature manually
- Vacation switching
- Group switching (multiple FRITZ!DECT 301 are combined in a group/room)
- Configurable temperature offset
- Recording of the temperature over the last 24 hours
- Display of the measured temperatures and configuration of the target temperature via FRITZ!Fon, the user interface of the FRITZ!Box or MyFRITZ!App
- Push service informs about loss of radio connection or low battery
- Intuitive setup in the browser using the FRITZ!Box user interface
- Control via PC, notebook, smartphone or tablet – even remotely over the Internet and the MyFRITZ!App
- Display content is rotatable in 90 degree steps
- Configurable open window detection
- Keylock – separately for radiator control and remote access

- Calcification protection
- Antifreeze function
- Secure integration in the home network via DECT ULE
- New features through automatic update function

Device properties

- Dimensions (W x H x D): 53 x 87 x 52 mm
- Weight: 143 g
- Batteries: 2 x AA/Mignon/LR6
- Radio standard: DECT ULE
- Radio range: up to 40 meters indoors
- Ready for operation in an ambient temperature between 0°C and 50°C

System requirements

- FRITZ!Box models with DECT (except FRITZ!Box 7312/7412)
- FRITZ!OS version 6.83 or higher

Package contents

- FRITZ!DECT 300
- Adapter for Danfoss RA/RAV/RAVL
- Batteries (2 x AA)
- Quick guide

Article number

- 20002822