

imagePROGRAF TM-255

PERFORMANCE REIMAGINED

Elevate printing experiences with enhanced productivity, intuitive functionality and professional image quality from a sustainable device. The 24" printer can seamlessly create accurate CAD prints with sharp lines and eye-catching marketing materials, designed for corporate and sizable AEC offices and the retail and education sector.

- Professional printing quality
 - Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials
- Enhanced productivity

Produce A1 CAD prints in just 20 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any sizes and easily meet higher print demand with larger ink tanks, quick processing time and a fast return from sleep mode

- Intuitive functionality
- Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touch screen panel. Save time by setting roll paper with quick access through a flat-top cover
- Improved sustainability

Environmentally conscious EPEAT Gold* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

*EPEAT Gold registered in the U.S.



TECHNICAL SPECIFICATIONS

imagePROGRAF TM-255

PRINTER TECHNOLOGY

Printer Type

Print Resolution Number of Nozzles

Line Accuracy

Nozzle Pitch Ink Droplet Size

Ink Capacity

Ink Type OS Compatability

Others supported job submission protocol Printer Languages

Standard Interfaces

Hard Drive

PRINTING SPEED CAD Drawing Plain paper (A1)

Poster

Plain paper (A1)

Heavy coated paper (A1)

MEDIA HANDLING Media Feed and Output

Media Width

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

Margins Printable area

Media Feed Capacity

PosterArtist

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head \times 1 print head)

2.400 x 1.200 dpi

Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560

 $\pm 0.1\%$ or less User adjustments necessary. Printing environment and media must match those used for the adjustments.

1.200 dpi x 2 lines minimum 5pl per colour

Bundled Starter Ink: 490ml (130ml for MBK, 90ml x 4 for BK, C, M, Y) Sales Ink: 300/130ml (MBK, BK, C, M, Y) Pigment inks: 5 colours MBK/BK/C/M/Y

32 Bit: Windows 7, Windows 8.1, Windows 10, 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows 10, Windows 10, Windows 52 core 2008 RZ, 2012, 2012RZ, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13

HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)

USB A Port: USB Memory (Direct Print)
USB B Port: Hi-Speed USB
Ethernet: IEEE802.3ab(1000base-T),
IEEE802.3(100BASE-TX)/IEEE802.3(10BASE-T)
Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

ase refer to user manual how to activate/deactivate the wireless LAN

28GB (Physcial memory 2GB)

500GB (Encrypted)

0:20 (Fast Economy Mode) 0:23 (Fast) 0:40 (Standard)

0:22 (Fast Economy Mode) 0:25 (Fast) 0:44 (Standard)

0:55 (Fast) 1:23 (Standard)

Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 - 610mm Cut sheet: 203.2 - 610mm Roll/Cut: 0.07mm - 0.8mm Roll paper: 203.2mm Cut sheet: 279.4mm

Roll paper: 18m (varies according to the OS and application)

Cut sheet : 1.6m

150 mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm

Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAl/Print): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm

Roll Paper: One roll Cut Sheet: 1 sheet

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

[Recommended] 515mm(JIS B2), 594mm (ISO A1), 10", 14", 17", 24"

[Printable] 257mm(JIS B4), 297mm(JSO A3), 329mm (ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm

Other than above, free size borderless printing is supported on only roll paper by user definition

Standard position: 1 sheet

Folding position: Plain paper 20 sheets on A1 portrait Flat position: Plain paper 20 sheets on A2 landscape (exclude strong curled position)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Accoustic Noise (Power/Pressure)

Regulations **Enviroment Certificates**

DIMENSIONS AND WEIGHT

Physical Dimensions and Weight

Packaged Dimensions and

WHAT'S INCLUDED What's in the Box?

Software Included

Optional Items

CONSUMABLES User Replaceable Items AC 100-240V (50-60Hz)

Operation: 64W or less Sleep mode: 2.2W or less

Default setting for the time to enter the Sleep mode: Approx. 5 minutes

Power off: 0.1W or less

Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation)

Operation:41dB(A), (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)

Standby: 35 dB(A) or less

Operation: 6.2 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)

CE mark, UKCA mark CB certfication, EPEAT GOLD

WxDxH

Main unit with stand

978 x 885 x 1060 mm (Operation panel is not tilted up/Basket Opened)

978 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed)

(including Roll Holder Set, excluding ink and print head)

Printer (Main unit with stand and pallet): 1152 x 913 x 946 mm, 96kg

Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB

Software available as Download from Web

2"/3" Roll Holder: RH2-28 IC Card Reader Holder: RA-02

Ink Tank: M:PFI-321(300ml) / PFI-121(130ml), MBK/BK/C/Y:PFI-320(300ml) / PFI-120(130ml)

Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

Footnotes

[1] EPEAT Gold registered in the U.S.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ** and **. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see









Canon Ireland 3006 Lake Drive

Co. Dublin, Ireland Telephone No: 01 2052400

Canon (UK) Ltd

The Bower 4 Roundwood Avenue Stockley Park Uxbridge **UB11 1AF**

Canon Inc. canon.com Canon Europe

canon-europe.com **English** edition © Canon Europa N.V.,2023



Citywest, Saggart Facsimile No: 01 2052525 canon.ie