

Rittal – The System.

Faster – better – everywhere.

Earth rail, vertical for VX, VX IT, TS, TS IT – DK 7547.000

Date : Jun 29, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES


FRIEDHELM LOH GROUP



Earth rail, vertical for VX, VX IT, TS, TS IT – DK

7547.000

created: 29.06.2021 on www.rittal.com/com-en



Product description

Description:	Easily fitted to the 25 mm DIN pitch pattern of distributors or to the 482.6 mm (19") mounting angles. The supplied earth conductors facilitate star earthing of the cable clamp straps in the patch panels. The earth terminals are fully adjustable. Current carrying capacity of rail approx. 200 A.
Supply includes:	Earth rail made from E-Cu 57 to DIN EN 12 163, DIN EN 13 601, 15 x 5 mm 16 push-in conductor connection clamps 1.5 – 16 mm² 15 earthing leads 6 mm², L = 500 mm Assembly parts

Product description

To fit:	Enclosure type: VX Enclosure type: VX IT Enclosure type: TS Height: 2000 mm
Dimensions:	Length: 1745 mm
Packs of:	1 pc(s).
Weight/pack:	2.81 kg
Copper weight (kg per piece):	0
EAN:	4028177131910
Customs tariff number:	74199990

ETIM 7.0:	EC000329
ETIM 6.0:	EC000329
eCl@ss 8.0/8.1:	27400605
eCl@ss 6.0/6.1:	27149205
Product description:	DK Earth rail, vertical, L: 1745 mm, For H: 2000 mm, For TS
Approvals	
Certificates:	EAC