Product data sheet

Specifications





APC Performance SurgeArrest 8 outlets 230V Germany

PM8-GR

Overview

Lead time

Main

Main Input Voltage	230 V
Cable length	2.00 m
Number of cables	1
Provided equipment	User manual

Physical

Colour	White
Height	6.17 cm
Width	32.65 cm
Depth	11.03 cm
Net weight	0.83 kg
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input power	2300 W
Network frequency	50 Hz
Maximum input current	10 A
Switching current capacity	10 A

Output

Number of power socket outlets	8
Outlet standard	Schuko CEE 7

Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	050000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	60 dB
Peak current	48 kAcommon mode 60 kA per phase normal mode
Surge energy rate	2690 J

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	36.5 cm
Package 1 Length	17 cm
Package 1 Weight	0.97 kg
SCC14	10731304313141

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	Limited Lifetime (European Union countries only)

Recommended replacement(s)