

SYSTEM XPC all-in-one POS P250

8 GB RAM, 120 GB M.2 SSD, no OS

COMPACT ALL-IN-ONE PC FOR POS AND CONTROL APPLICATIONS

The Shuttle POS P250 is an all-in-one system without operating system. It comes with a 11.6" multi-touch display and is positioned as a space-saving POS system or control device for media playback or automation. The adjustable stand allows for flexible viewing and operation angles, while it can also be VESA-mounted to appropriate stands or walls. The front panel is protected from splashing of water and dust according to the IP54 rating. A cable collector box on the back side helps avoid clutter. Thanks to its passive cooling, the system is virtually noise-less, maintenance-free and approved for 24/7 nonstop operation.



TOUCH SCREEN



SUPPORTS 16 GB DDR5



HDMI 2.0b and VGA Ports



Full-HD WEBCAM



NVMe SSD SUPPORT



2.5" BAY



INTEL 2.5G LAN



DUAL COM PORTS



75x75 mm VESA MOUNT



IP54 Front



Max. 40 °C



24/7 SUPPORT

COMMON FEATURES

- IP54 compliant front panel ■ Dimensions: 299 x 207 x 59 mm (WHD)
- Supports 24/7 Nonstop Operation ■ 75x75 mm VESA mount capable
- Operating temperature: 0~40 °C ■ Fanless heatpipe cooling system

DISPLAY & GRAPHICS

- 29.5 cm (11.6") LC Display, 1366 x 768 pixel, 250 Nits ■ Capacitive 10-point multitouch screen ■ Integrated graphics ■ HDMI 2.0b & VGA

OPERATING SYSTEM

- An operating system is not included
- Supports Windows 10/11 (64-bit) and Linux (64-bit)

PROCESSOR

- Intel N100, Quad Core, clock rate: 3.4 GHz, 6 MB Cache
- Intel Generation 12 "Alder Lake-N" TDP: 6 W

STORAGE (not included)

- 8 GB DDR5-4800 SO-DIMM memory
- 120 GB SSD in M.2-2280 format, supports PCIe/ NVMe
- Supports one 2.5" SATA hard disk/SSD, max. 9 mm in height

CONNECTIVITY

- HDMI 2.0b ■ D-Sub/VGA ■ 2x USB 3.2 Gen 2 (10 Gbps) ■ 4x USB 3.2 Gen 1 (5 Gbps) ■ Gigabit 2.5G LAN (Intel 226LM) ■ 2x RS232 COM ports
- 2x Audio (Mic & Headphones) ■ Power Button ■ Power and HDD LED
- Hole with Clear CMOS Button ■ DC-in (2.5/5.5 mm, supports 12&19V)

NETWORK

- 2.5 Gbps LAN, Intel 226LM Ethernet Controller
- Built-in: WLAN card RTL8821CE supports WLAN 802.11ac (WiFi 5) and BT 4.2 with 2 internal antennas

BUILT-IN

- 1080p (2 MP) Full-HD webcam
- 2 W speaker ■ Electret Condenser Microphone

POWER SUPPLY

- External 65W / 19V power adapter

OPTIONAL ACCESSORIES

- **WLN-M1:** WLAN Upgrade Kit with WLAN card Intel AX200 supports WLAN 802.11ax (Wi-Fi 6) & BT 5.2 with two external antennas

MODELS OF THE P25N SERIES

Product	Type	Processor	RAM	M.2 SSD	Operating System	Bar Code
P25N	Barebone	Intel N100	—	—	—	887993006536
POS P250	Complete system without OS	Intel N100	8 GB DDR5	120 GB	—	4046047104123
IoT P2500PA	Complete system with OS	Intel N100	8 GB DDR5	120 GB	Win10 IoT Enterprise 2021	4046047104130
P2500T	BTO System Configuration	Intel N100	BTO	BTO	BTO	—



Front and Back Panel



- | | | |
|---|---|---------------------------------------|
| 1. 2x Perforation for optional antennas | 11. Power-on button | 20. 2x serial COM port (D-Sub, RS232) |
| 2. Hole for Kensington lock | 12. Microphone input | 21. D-Sub/VGA video output |
| 3. Line Collector Box | 13. Audio Line-out (headphones) | 22. 4x USB 3.2 Gen 1 (5 Gbps, blue) |
| 4. Detachable stand | 14. Hole with Clear CMOS button | 23. 2.5G LAN port (RJ45) |
| 5. Webcam | 15. 2x USB 3.2 Gen 2 (10 Gbps, red) | 24. HDMI video output |
| 6. LED Indicator for Webcam | 16. Detachable chassis cover | 25. DC-input for power adapter |
| 7. Multi-touch LCD display | 17. Detachable VESA cover | 26. 2x rubber foot |
| 8. Microphone | 18. Mono speaker (2 W) | |
| 9. Power-on LED | 19. Screw holes according to the 75x75 mm VESA mount standard | |
| 10. Hard disk LED | | |

Product Comparison: Shuttle XPC All-in-One Models

Chassis	Display Pixel / Type	CPU Type	Product Name by Intel processor-generations				Chassis Colour
			Gen. 7 Kaby Lake	Gen. 8 Whiskey Lake	Gen. 10 Comet Lake	Gen. 12 Alder Lake	
	11.6" 1366 x 768 Capacitive Multitouch	Celeron or N100	P20U	—	P22U	P25N	Black
	15.6" 1366 x 768 Resistive Singletouch	Celeron	X50V6	X50V7 X50V7L *)	X50V8	X50V9	Black, White
		Core i3	X50V6U3	X50V7U3 X50V7U3L *)	X50V8U3	X50V9U3	Black, White
	15.6" 1920 x 1080 Capacitive Multitouch	Celeron	—	P51U	P52U	TBA	Black
		Core i3	—	P51U3	P52U3	TBA	Black
	19.5" 1600 x 900 Capacitive Multitouch	Celeron	P90U	—	P92U	—	Black, White
		Core i3	P90U3	—	P92U3	—	Black, White
		Core i5	P90U5	—	P92U5	—	Black

X50V7L and **X50V7U3L** are model variants without WLAN module

SHUTTLE XPC all-in-one System POS P250 – SPECIFICATIONS

FANLESS AND SILENT	<p>Passive heatpipe cooling, absolutely no fan noise</p> <p>Perfect for noise-sensitive environments</p> <p>Fanless, dust-free and thus virtually maintenance-free</p>
24/7 NONSTOP OPERATION	<p>This device is approved for 24/7 permanent operation. Requirements:</p> <ul style="list-style-type: none"> - Free circulation of air amongst the PC must be guaranteed. - Ventilation holes must be kept clear. - If a hard disk is installed, this must also be approved for permanent operation by its manufacturer.
IP54 PROTECTED	<p>The front panel is dust-protected and protected from splashing of water according to protection class IP54.</p>
CHASSIS	<p>Colour: black</p> <p>Dimensions: 29.9 x 20.7 x 5.9 cm (W x H x D)</p> <p>75x75 mm VESA mount capable</p> <p>Mounting hole for Kensington lock</p> <p>Weight: 1.95 kg net, 3.14 kg gross</p>
OPERATING SYSTEM	<p>This system comes without operating system.</p> <p>It is compatible with:</p> <ul style="list-style-type: none"> - Windows 10/11 - 64-bit - Linux - 64-bit
TOUCHSCREEN	<p>Touchscreen function supports fingertip input</p> <p>Capacitive Touch Panel with 10-point multi-touch</p> <p>Supports input with gloves (PVC, cotton, cotton/linen)</p> <p>Stylus pen not supported</p>
11.6" DISPLAY	<p>29.5 cm / 11.6" LCD TN display</p> <p>Aspect ratio: 16:9 widescreen</p> <p>Resolution: 1366 x 768 = 1.05 Megapixel</p> <p>Backlight unit: LED, Luminance: 250 cd/sqm (typ.)</p> <p>Glass thickness: 3 mm</p>
PROCESSOR	<p>Model: Intel N100</p> <p>System-on-a-chip architecture (SoC): no chipset required</p> <p>FCBGA1264 package - directly soldered onto the mainboard</p> <p>Code name: Alder Lake-N (12th Generation Intel Core)</p> <p>Cores / Threads: 4 / 4</p> <p>Turbo clock rate: max. 3.4 GHz</p> <p>Smart Cache: 6 MB</p> <p>TDP wattage: 6 W</p> <p>Manufacturing process: Intel 7</p> <p>Maximum Tjunction Temperature: 105 °C</p>
INTEGRATED GRAPHICS	<p>Intel UHD Graphics</p> <p>GPU clock frequency: max. 750 MHz</p> <p>Execution Units (EUs): 24</p> <p>Supports DirectX 12.1</p>
SUPPORTS TRIPLE DISPLAY	<p>Two video ports support two additional independent screens:</p> <ol style="list-style-type: none"> 1) HDMI 2.0b supports 3840 x 2160 @ 60 Hz 2) VGA / D-Sub analog video supports 1920 x 1080 @ 60 Hz <p>Special conditions for operation in Multi-Monitor mode:</p> <ol style="list-style-type: none"> 1) Clone mode: all displays show the same content at 1366x768 resolution 2) Extended mode: all displays show different content
BIOS	<p>AMI BIOS in 32 MByte EEPROM with SPI interface</p> <p>Supports Power fail resume / always on</p> <p>Supports Wake-on-LAN (WOL) from S3, S4, S5 ACPI states</p> <p>Supports hardware monitoring and Watchdog functionality</p> <p>Supports Firmware TPM v2.0 functionality</p>
MEMORY	<p>8 GB DDR5-4800 (PC5-38400) SDRAM i SO-DIMM format</p> <p>This PC supports a maximum capacity of 16 GB</p>
M.2-SSD CARD	<p>120 GB SSD flash memory</p> <p>M.2-2280 card with PCI-Express interface supports NVMe</p>

2.5" BAY FOR HDD/SSD	Supports one SATA hard disk or one SATA SSD drive in 6.35 cm / 2.5" format The SATA 3.0 interface supports up to 600MB/s data transfer speed (6 Gbit/s) Supports one drive with up to 9.5 mm in height SATA cable pre-installed
WEBCAM	Integrated Full HD webcam (1920 x 1080 pixels = 2 MP)
MICROPHONE AND SPEAKERS	With integrated Electret Condenser Microphone and 2 W speaker
INTEGRATED AUDIO	Realtek ALC888S (HD-Audio) Two analog audio connectors (3.5 mm) on the left side: 1) Line-out (head-phones) 2) Microphone input Digital multi-channel audio output is supported via HDMI.
WIRED NETWORK	Intel i226LM Ethernet Controller Supports 10 / 100 / 1.000 / 2500 Mbps operation Supports WAKE ON LAN (WOL) from S3/S4/S5 modes Supports network boot by Preboot eXecution Environment (PXE)
WIRELESS NETWORK (WLAN)	Built-in M.2-2230-E WLAN card with two internal antennas WLAN Controller Realtek RTL8821CE Supports WiFi IEEE 802.11b/g/n/ac on the 2.4 / 5 GHz band, 1T1R Supports 20 / 40 / 80 MHz channel bandwidth Security: supports WPA(-PSK), WPA2(-PSK), WEP 64/128 bit, IEEE 802.11x, IEEE 802.11i Supports Bluetooth 4.2 on the 2.4 GHz band
HOLES FOR OPTIONAL ANTENNAS	The chassis features two perforated 6.5 mm holes for optional antennas mounted with an (RP-)SMA connector for wireless network such as WLAN
FRONT LEDs	Power LED (blue) Hard disk LED (orange)
CONNECTORS LEFT SIDE	Power button 2x USB 3.2 Gen 2 (type A, red, max. 10 Gbps) Audio Line-out / headphones (3.5 mm jack) Microphone input (3.5 mm jack) Hole with Clear CMOS button
CONNECTORS RIGHT SIDE	Mounting hole for Kensington lock
CONNECTORS BOTTOM SIDE	HDMI 2.0b (supports digital video and digital audio) VGA connector (D-Sub 15 pol., analog video) 4x USB 3.2 Gen 2 (type A, blue, max. 5 Gbps) 2.5G Network (LAN, RJ45) 2x COM port (RS232) DC input for external power adapter (5.5 / 2.5 mm)
POWER ADAPTER	External 65 W power adapter (fanless) Input: 100~240 V AC, 50/60 Hz, max. 1.6 A Output: 19 V DC, max. 3.42 A, max. 65 W DC cable, ca. 170cm, 5.5 / 2.5 mm plug AC cable, ca. 170 cm, 3-pin Micky MM C6 and Schuko earthed safety plug
DC INPUT CONNECTOR	DC Input Connector: 5.5 / 2.5 mm (outer/inner diameter) The DC-input of the computer supports an external power source with either 12V ±5 % or 19V ± 5%.
SUPPLIED ACCESSORIES	Quick Installation Guide Windows 10/11 Driver DVD External Power Adapter (65W / 19V) with 3-pin AC cable
OPTIONAL ACCESSORIES	WLN-M1: WLAN kit with Intel AX200 WLAN card (supports WLAN-ax / Wi-Fi 6) and two external antennas <u>Note:</u> a WLAN-ac / Wi-Fi 5 module with two internal antennas is already pre-installed by default.
ENVIRONMENTAL SPECIFICATIONS	Operating temperature: 0~40 °C Humidity: 10~90 %
CERTIFICATIONS / COMPLIANCE	EMI: CE, UKCA, FCC, BSMI, RCM, VCCI Safety: CB (IEC 60950/62368), cTUVus (UL 62368-1:2014), BSMI Other compliances: RoHS, ErP Lot3, Energy Star v8.0


CONFORMITY

This device is classed as a technical information equipment (ITE) in class B and is intended for use in living room and office.


The CE-mark approves the conformity by the EU directives:

- (1) 2014/30/EU relating to electromagnetic compatibility (EMC),
- (2) 2014/35/EU relating to Electrical Equipment designed for use within certain voltage limits (LVD),
- (3) 2009/125/EC relating to ecodesign requirements for energy-related products (ErP)
- (4) 2014/53/EU Radio Equipment Directive (RED)

P25N Drawings with stand



P25N Drawings without stand



© 2024 Shuttle® Computer Handels-GmbH – All information subject to change without notice. Optional components and accessories are not included. Pictures for illustration purposes only.