

4K PTZ Camera

No.: 38422

High performance PTZ camera for UC spaces in education, boardrooms or training rooms

Description

- High performance, professional USB PTZ camera for meeting rooms or hybrid education spaces
- Support 4K resolutions for superior clarity of video recording
- 3x Optical Zoom for high quality close-up viewing
- AI voice and speaker tracking
- 3 year Warranty

The Lindy 4K PTZ (Pan, Tilt, Zoom) camera is a high-performance solution for capturing superior quality video in a variety of conferencing or hybrid settings such as lecture theatres, boardrooms, medical suites or training facilities. With the included USB cable, the camera can be easily connected to a USB PC, Hub or extension system.

Superior 4K Clarity

Equipped with a built-in 4K dual-eye PTZ camera system, featuring a 120° panoramic lens for real-time participant detection and a 4K PTZ camera with 3x optical zoom and 110° field of view. Capture every person in the room with stunning clarity and enjoy high-quality images even when zooming in.

AI-Powered Video Conferencing Made Easy

Experience automatic AI-powered auto framing, speaker tracking, and presenter tracking. Instantly capture all meeting attendees in real-time as the system automatically adjusts to people entering or leaving the room. Built-in microphone* arrays enable the camera to focus on the active speaker with dynamic close-ups, while advanced presenter tracking keeps the presenter always centered. Elevate your meetings with smart, seamless video technology.

Wired Compatibility

The USB A to C cable can easily be connected to a USB source and integrated with many popular software platforms including Zoom and Microsoft Teams for an immersive video conferencing experience.

Enhanced Conference Viewing with Dual-Lens PIP and AI Smart Gallery

Enjoy flexible picture-in-picture layouts that display both speaker/presenter and wide-angle views simultaneously perfect for medium to complex meeting spaces. AI-powered Smart Gallery technology automatically crops and highlights participants, delivering clear, individual video feeds for more engaging and effective hybrid meetings.

*The four integrated microphones are used only for the voice detecting and tracking (They can not be used as video conference audio source)

Technical details

Specifications

- Resolution: 3840x2160@30Hz
- Sensor: -
- Pixels:
  - Main Lens: 8 Megapixel

Panoramic Lens: 2 Megapixel
Diagonal Field of View: 110°
Horizontal Field of View: 75°
Vertical Field of View: 35°
Focal Length: -
Aperture: -
Minimum Illumination: -
White Balance: Automatic
Gain Control: Automatic
Backlight Compensation: Automatic
Electronic Shutter: Automatic

Connectors

Input: USB Type C (Female), USB Type A (Female)
Power: 3.5/1.35mm

Physical Properties

Dimensions (approx.) WxDxH: 100.4x200x69mm (3.95x7.87x2.72in)
Housing Material: Metal & Plastic
Net Weight: 0.44kg (0.97lb)
Operating Temperature: 0°C - 40°C (32°F - 104°F)
Storage Temperature: -20°C - 60°C (-4°F - 140°F)
Humidity: 10 - 90% RH (non--condensing)
Input Voltage: DC12V 3A
Power Consumption: 10W
Colour: Black
Installation: Mountable

Miscellaneous

Packaging Type: Carton Box
Packaging Dimensions: 150x355x125mm (5.91x13.98x4.92in)
Gross Weight: 1.48kg (3.26lb)
Warranty (Years): 3
Certificated: CE, UKCA, FCC, RoHS & REACH

Package Contents

USB PTZ Camera
Installation Kit with Screws
IR Remote Control
USB Type A to Type C Cable, 1.5m
12VDC 3A Power Supply
Lindy Manual

Purchasing Information

No.: 38422
EAN: 4002888384223

© LINDY 2026