

Eaton EVMAF332X

Catalog Number: EVMAF332X

Eaton Managed G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 42 outlets (24)C13, (18)C39

General specifications



Product Name	Catalog Number
Eaton Rack PDU G4	EVMAF332X
Model Code	EAN
PDU G4 MA 0U 309 32A 3P 24xC13,18xC39	3553340696930
	Product Length/Depth
	1730 mm
Product Height	Product Width
53 mm	52 mm
Product Weight	Compliances
6.6 kg	CB LVD Directive RoHS Directive WEEE Directive Packaging Directive

Certifications
IEC 62368-1
EN IEC 63000
CISPR 35/EN 55035
CE
EAC
UKCA
Cm
Ukr
IEC/EN 61000-6-2
IEC/EN 61000-6-4
IEC 61000-3-11
IEC 61000-3-12

Special features

Remote Site Management
Versatile C39 outlet
supports C14 or C20 power cord plug
High retention outlets
designed to securely fit standard power cords and support P-Lock power cords
Cybersecurity standards UL 2900-1 and IEC 62443-4-2
Hot-Swap network control module
Network Cascading, connect up to 32 PDUs via network loop
Power sharing between two network modules PDUs ensures constant access to PDU data & sensors
1% IEC Class 1 billing grade measurement accuracy
Gigabit network card with 2x Gb ports
Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS
1% measurement accuracy at the outlet level (V, W, A)
Outlets control for On/Off, reboot, and sequential start-up capabilities

Type

Managed Rack PDU

Form factor

0U (Vertical)

Outlet control

Yes

Accessories

Rack PDU
Rack mounting accessories
Quickstart guide

Brochures

[Rack PDU G4 Brochure EN](#)

Declarations of conformity

[EU declaration of conformity Rack PDU G4](#)

Drawings

[Technical drawing](#)

Safety Instructions

Operating Temperature

0° to 60°C (32° to 140°F)

Mounting direction

Vertical

Color

Black

Material

Aluminium

Input connection

IEC-60309 32A 3Ph

Cord length

3m

Wattage

22 kW max

Amperage Rating

32 A

Input voltage

240/415V

Phase

Three-phase

Frequency rating

50/60 Hz

Outlets

(24) C13, (18) C39

Number of Outputs 5-15R

0

Number of Outputs 5-20R

0

Number of Outputs 6-15R

0

Number of Outputs 6-20R

0

Number of Outputs L14-30R

0

Number of Outputs L5-20R

0

Number of Outputs L5-30R

0

Number of Outputs L6-20R

0

Number of Outputs L6-30R

0

Number of Outputs C13

24

Number of Outputs C19

18

Number of Outputs C20

0

Number of outputs hardwired

0

Num of Outputs PC (SCHUKO)

0

Number of outputs (other)

18

Number of outlets with earth pin

42

No of Outlet Suisse Stndrd Type13

0

No of Outlet Suisse Stndrd Type15

0

No of Outlet Suisse Stndrd Type23

0

No of Outlet Suisse Stndrd Type25

0

Number of UK BS1363 sockets

0

SNMP

Yes

Ethernet interface

Yes

Serial interface

Yes

Mass configuration

Yes

Electrical connection

Connecting cord with plug

Evaluation

At distance

Mounting Dimension (metrical)

52

Mounting dimension (standardized)

Metric

Switchable

Yes

Over voltage category

2

Series

G4



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)