Product datasheet

Specifications



APC NetShelter Rack PDU Advanced Gen 2, Switched, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 530P6, 48 Outlet

APDU11350SW

Main

Product or component type	PDU
Main Input Voltage	415 V 3 phases 400 V 3 phases
Input current limits	30 A
Network frequency	50/60 Hz
Main Output Voltage	240 V
Input Connection Type	IEC 60309 30 A 3P + N + PE
Number of power socket outlets	24 C13/C15/C19/C21 24C13/C15
Load capacity	17300 VA
[In] rated current	24 A
permissible voltage	200…240 V 346…415 V
Max current draw	24 A
PDU type	Switched
Protection type	Circuit breaker
Number of rack unit	0U
Cable length	3 m

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
Height	1780 mm
Width	56 mm
Depth	75 mm
Net weight	9.6 kg

Environmental

Product certifications	UKCA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
IP degree of protection	IP44
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	198 cm
Package 1 Width	13.2 cm
Package 1 Length	26.2 cm
Package 1 Weight	12.6 kg

Logistical informations

Country of origin	US

Contractual warranty

Warranty (in months)	36

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**31346aed-552c-4a16-81d9-e683a383b6da**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Removable battery	**No**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative





Product datasheet APDU11350SW





Product datasheet APDU11350SW

