

LCD 98" Message Large Format Display

Sharp MultiSync® M982



Built to perform, designed to last

The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments. With native USB-C connectivity and broad compatibility with platforms such as Crestron, Cisco Webex, and Microsoft Teams, it enables seamless BYOD collaboration and future-ready integration, while 802.1x LAN support ensures enterprise-grade network security. Featuring class-leading 550 cd/m² brightness, a high-haze panel to minimise glare, and NEC's trusted SpectraView Engine, the M2 Series delivers outstanding visual performance with unmatched colour precision.

As part of the new Sharp-branded display family, the MultiSync® M2 Series builds on NEC's legacy of quality and reliability to drive greater efficiency and long-term value. Its proven modular design supports custom computing options (Raspberry Pi or Intel® SDM) and flexible connectivity (e.g. AV-over-IP), ensuring lasting versatility, performance, and sustainability.

Benefits

Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.

Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment

Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.

Enhanced imaging precision – when brand consistency and corporate identity are important, NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.

Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration and future-proof scalability.

Specifications

Product Information

Product Name

Sharp MultiSync® M982

Model

PN-M982

Product Group

LCD 98" Message Large Format Display

Order Code

60006059

Display

Panel Technology

IPS with Direct LED backlights

Screen Size [inch/cm]

98 / 247.7

Aspect Ratio

16:9

Brightness [cd/m²]

550

Contrast Ratio

≥ 8000:1¹

Viewing Angle [°]

178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

Colour Depth [bn]

1.073 (10bit)

Colour Gamut

72% of NTSC

Response Time (typ.) [ms]

8

Panel Refresh Rate [Hz]

60

Haze Level [%]

Pro (25)

Supported Orientation

Face Up²; Landscape; Portrait

Resolution

Native Resolution

3840 x 2160

Supported Resolutions

| | | |
|--------------|--------------|--------------|
| 1024 x 768; | 1440 x 900; | 4096 x 2160; |
| 1270 x 720; | 1600 x 1200; | 640 x 480; |
| 1280 x 1024; | 1680 x 1050; | 720 x 400; |
| 1280 x 720; | 1920 x 1080; | 720 x 480; |
| 1280 x 800; | 1920 x 1200; | 720 x 576; |
| 1360 x 768; | 1920 x 1200; | 800 x 600 |
| 1366 x 768; | 1920 x 2160; | |
| 1400 x 1050; | 3840 x 2160; | |

Synchronisation Rate

Horizontal Frequency [kHz]

15 - 135

Vertical Frequency [Hz]

23 - 76

Connectivity

HDMI IN 1

Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; ARC; CEC

HDMI IN 2

Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; CEC

HDMI OUT

Video Output; UHD (60 Hz) HDCP (2.2); Audio Output; Loop Through: HDMI IN 2, Option, Compute module

DP IN 1

Video Input; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Input

DP OUT

Video Output; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Output; Loop Through: DisplayPort IN, USB-C 2

USB-A 1

USB (2.0 / 3.2); 4.5 W; Peripherals; USB Storage

USB-A (Service)

2.5 W; Service

USB-C 1

Video Input; UHD (60 Hz); DP alt. 1.2; HDCP (2.2); Audio Input; USB 2.0 / 3.2; 65 W

USB-C 2

USB 2.0 / 3.2; 7.5 W; Peripherals; Storage

Audio Output (3.5 mm)

Audio Output; Line Out

LAN 1

100 MBit/s

LAN 2

Loop Through: LAN 1, RS-232C, IR; 100 MBit/s

RS-232C

9600 bps

Remote In (3.5 mm)

Eco Sensor (IR-Extender, Ambient and Presence)

Input Detect

Custom; Last; First

PiP / PbP

2-Split; Scalable picture size

Calibration

Factory Calibration

Gamma; Intensity; RGB; Uniformity; White Point

Calibration with Software

Corner Uniformity; Gamma; Intensity; RGB; Update Factory Calibration; White Point

Calibration Software

Display Wall Calibrator

Open Modular Intelligence

Intel® SDM

accepts Intel® Smart Display Modules Large and Small up to 66 W

Compute Module Slot

MPI4 and MPI5 Kit (powered by Raspberry Pi)

Sensors

Ambient Light Sensor

Integrated, triggered actions programmable

Human Sensor

optional via Eco Sensor (KTES1)

Temperature Sensor

Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption [W]

210 shipping

Power Savings Mode [W]

< 0.5; < 2 (Networked Standby)

Power Management

VESA DPMS

Power Supply

100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]

+0 to +40

Operating Humidity [%]

20 to 80

Storage Humidity [%]

10 to 80

Storage Temperature [°C]

-20 to 60

Mechanical

Dimensions (W x H x D) [mm]

2,194.7 x 1,250.2 x 84.3

Weight [kg]

68

Bezel Width [mm]

15.9

VESA Mounting [mm]

4 holes; 600 x 400 (FDMI); M8

Ingress Protection

IP5x (front); IP2x (back)

Packaging Dimensions (W x H x D) [mm]

2,350 x 1,400 x 310

Packaging Weight [kg]

99

Material

Metal

Available Options

Accessories

Eco Sensor (KTES1); Feet (ST-801); Remote control kit (KTRC3); Speaker (SP-RM3a); Trolley (L20PNSR780MEU); USB-C cable (USB-C 5M, USB-C 7M); Wall mount (L20PNWALL90EU, SF680P)

Regulatory

Safety and Ergonomics

CE; EMC Class B; Energy Star 8; FCC Class B; REACH; RoHS; UKCA; UL/C-UL or CSA

Pixel Failure Class

ISO 9241-307, Class 1

Resistance to Fire

Metal backcover, plastic material certified acc. to UL94-5VB

Green Features

Energy Efficiency

Energy consumption: 202 kWh/1000 h; Energy efficiency class: G; LED backlight

Ecological Standards

EnergyStar 8.0

3rd Party Certifications

Crestron

Certified for Crestron CCV2 and XiO Cloud

Additional Features

Special Characteristics

CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler

Colour Versions

Black Front Bezel, Black Back Cabinet

Audio

Integrated Speakers (10 W + 10 W)

Shipping Content

2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual

Warranty

3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension³

Operating Hours

24/7

External Control

AMX NetLinx Support; Crestron V2; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP

Remote Management

NaViSet Administrator 2

Security

Disable HW Buttons; Disable IR Functionality; Emergency Notification; IEEE802.1X (LAN)

¹ out of the box conditions, local dimming ON

² adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

³ please refer to terms and conditions of warranty extensions



RoHS



CE

FCC Class B

This document is © 2025 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 21.11.2025