

Overview

Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy

The Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy represents a composable and integrated Fibre Channel interconnect module with Gen6 technology that simplifies integration of the HPE Synergy blade chassis into a Storage Area Network (SAN). It provides breakthrough application performance, operational stability and simplified manageability to meet the stringent business requirements with 32Gb FC technology for HPE's Composable Infrastructure. It is ideal for enterprises planning to deploy 32Gb FC to meet growing bandwidth demands of high-density virtualization/applications utilizing All-flash Storage arrays (AFA) and for customer looking to deploy scalable private cloud storage networks using HPE Synergy for workloads.

Brocade 32Gb FC Switch for HPE Synergy provides industry-leading performance with <900ns frame latency for fast switching, switching bandwidth up to 896 Gbps and a maximum throughput of 512 Gbps to enable demanding applications and high-density server virtualization. It provides scalability with 16 external optical ports (2 QSFP ports and 8 SFP+ ports) each supporting 32Gb, 16Gb and 8Gb FC speeds that customers can utilize on-demand paralleling their business growth. The QSFP ports support a break-out cable for connection to standard SFP+ ports. It provides simplified manageability utilizing the advanced Web Tools to simplify fabric set-up and on-going maintenance for SAN administrators. The Power Pack+ SAN management software option enables customers to manage data flow and maintain optimized application performance. With the HPE PowerPack+ software, the customers can also utilize IO Insight software for proactive and real-time monitoring of storage and application-level IO and VM Insight software to optimize VM workloads and ensure service-level objectives are met. Brocade 32Gb FC Switch Module for HPE Synergy is NVMe ready and provides next-generation storage connectivity to existing storage network. This will help customers transition applications and dynamically migrate to NVMe on demand continuing with the existing 16Gb and 32Gb SAN to run NVMe without code changes. Brocade 32Gb FC Switch Module for HPE Synergy also lowers TCO as it hot-plugs into the back of the HPE Synergy Frame. This frees-up rack space, enables shared power and cooling, and reduces cabling resulting in significant infrastructure savings.



Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy

At a Glance**Integrated SAN connectivity**

Enables data center consolidation with HPE Synergy through a state-of-the-art zero-footprint design while lowering cost through shared power and cooling, fewer cables and less space resulting in reduced infrastructure complexity and lower operations costs.

32 Gb FC storage networking

Enables support of virtualized environments and other emerging technologies through high-speed technology that doubles the performance of the storage network. External facing ports auto-sense lower bandwidth components for flexibility and investment protection with existing FC ports (8, 16 or 32Gbps FC for external ports) as well as to the future FC products (64Gbps).

Overview

Quad Small Form-factor Pluggable (QSFP)

Up to two 4x32 Gbps QSFPs are supported, which can be used as additional 32 Gbps FC ports, 128 Gbps high speed FC ISL ports between switch modules, or as part of 128Gbps trunk port to a B-series Director.

Non-blocking architecture

Includes connection speed support for all ports to provide a high-performance system with switching bandwidth of up to 896 Gbps (28 ports x 32 Gbps).

ISL Trunking performance enhancements

Support for multiple trunks, with the maximum trunk size of up to eight SAN ports for up to 256Gbps balanced throughput per each trunk group. Trunking of the SAN-facing ports with external Brocade or HPE B-series switches provides a high-bandwidth solution while lowering costs through fewer SFPs and cables. You can trunk up to 8 external FC SFP+ ports or up to two QSFP ports. For maximum flexibility any number of consequent ports within adjacent QSFP ports can form a trunk.

Fabric Vision

Enables powerful built-in monitoring SAN management, and diagnostic tools to simplify administration, increase uptime and reduce costs. This results in significant insight and visibility across SANs with extensive analytics to keep your SAN optimized for best results. Available by default in the Power Pack+ model or as an upgrade option. It enables IO Insight and VM Insight Software.

Access Gateway mode

Employs N_Port ID Virtualization (NPIV), an ANSI T11 standard, to enable interoperability with other SAN fabrics and eliminate domain considerations while improving SAN scalability.

Broad range of management tools and SMI-s conformance

Integrates with HPE OneView for monitoring and leverages HPE B-series SAN management and monitoring tools (PowerPack+, Fabric Vision). New REST API in addition to existing SMI-s API enables the use of industry standard interfaces to integrate management with other applications.

Utilizes advanced Web Tools to simplify fabric set-up and on-going maintenance for SAN administrators.

Switch Configuration-available in three base models

Available in 12-port, 20-port and 20-port Power Pack+ Full Fabric models. Choose the features and management options that make sense for your needs.

What's New

- Introducing HPE SANnav Management Software support for active manageability
 - New 32 Gb/s Fibre Channel embedded high performance switch module for HPE Synergy Frame
 - 12 downlink internal server ports, up to 8 uplink (SFP+) external ports and 2 uplink (QSFP) external ports
-

Standard Features

Advanced Fabric Services

- Hardware Enforced Zoning*
 - Dynamic Path Selection*
 - Web Tools
 - Power Pack+ fabric services software bundle (optional)
 - Fabric Vision (Includes IO Insight and VM Insight Software)
 - ISL Trunking
 - Extended Fabrics*
- Notes:** *Not supported in Brocade Access Gateway mode.

Manageability

- Web Tools
- HPE Storage Operations Orchestration (optional)
- SMI API
- SNMP
- REST API
- PyFOS
- SAN automation with Ansible

Interoperability

Brocade Access Gateway mode enables the Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy to interoperate with other SAN fabrics running supported firmware. While in Access Gateway mode, the device must be connected to an NPIV-enabled edge switch or director. Supported edge environments are listed in the SAN Design Guide

<https://support.hpe.com/hpsc/doc/public/display?docId=c00403562>

Software Components, Standard

Access Gateway*

Brocade Access Gateway Mode enables seamless connectivity for the Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy to other supported SAN fabrics, enhances scalability and simplifies manageability. Utilizing N_Port ID Virtualization (NPIV) standards, Brocade Access Gateway eliminates switch/domain considerations.

Notes:*Brocade Access Gateway mode does not support switch-related features, including some features in the Power Pack+ bundle (e.g. Extended Fabric). Please refer to the Access Gateway Administrator's Guide for details.

Frame Filtering

A special B-Series ASIC-based capability that enables new applications and features. The switch has the ability to "view" the first 64-bytes of the Fibre Channel frame. At this time, Frame Filtering enables advanced capabilities such as Advanced Zoning, Frame level analytics and statistics.

Advanced Zoning

Zoning (Port and Worldwide Name), as well as Access Control, are enforced by hardware within the ASIC. Hardware enforcement enables the highest level of zoning enforcement without any impact to performance. Administrators can organize a physical fabric into logical groups and prevent unauthorized access by devices outside the Zone.

Standard Features

Web Tools

Enables organizations to monitor and manage single Fibre Channel switches and monitor small SAN fabrics. Tasks can be performed through a Java-capable Web browser from a standard laptop, desktop PC or workstation from any location within the enterprise.

Dynamic Path Selection

Improves performance by dynamically routing data traffic across multiple links and trunk groups.

Adaptive Networking Services

Adaptive Networking services optimize fabric behavior and ensure ample bandwidth for mission-critical applications. The tools currently include Quality of Service (QoS), Ingress Rate Limiting and Traffic Isolation. By assigning zones a high, medium, or low priority, QoS allocates bandwidth in the event of congestion to expedite high-priority traffic and keep all traffic flowing. Ingress Rate Limiting restricts data flow from less-critical hosts at preset bandwidths. Traffic Isolation assigns high-bandwidth data flows to specific ISLs.

Notes: Adaptive Networking Services are included by default in the switch firmware and do not require a separate license.

Software Components, Optional

Power Pack+ Software Bundle

The Power Pack+ Software Bundle includes:

- Fabric Vision (Includes IO Insight and VM Insight Software)
- ISL Trunking
- Extended Fabrics*

Notes:

- *Not supported in Access Gateway mode (see the Access Gateway Administrator's guide for full details).
- Adaptive Networking and Server Application Optimization features are included by default in the switch firmware and do not require a separate license

Fabric Vision

Fabric Vision offers innovative diagnostic, monitoring and management capabilities to help accelerate new application deployments, address SAN problems before they impact operations and reduce operational costs, it Includes:

- VM Insight: Seamlessly monitors end-to-end VM performance through standards-based VM tagging
- IO Insight: Automatically detect degraded storage IO performance with integrated device latency and IOPS monitoring
- Monitoring and Alerting Policy Suite:
A policy-based monitoring tool with pre-built rules and automation that simplifies fabric-wide threshold configuration and monitoring. In addition, administrators can include IO Insight metrics in MAPS policies to understand IO profile as well as to be notified of storage IO performance degradation.
- Configuration and Operational Monitoring Policy Automation Services Suite (COMPASS):
Simplifies deployment, safeguards consistency and increases operational efficiencies of larger environments with automated switch and fabric configuration services. Administrators can configure a template or adopt an existing configuration to seamlessly deploy a configuration across the fabric.
- ClearLink® Diagnostics:
Ensures optical and signal integrity for Fibre Channel optics and cables, simplifying deployment and support of high-performance fabrics. ClearLink Diagnostic
- Port (D_Port) is an advanced capability of Fibre Channel platforms.
- Flow Vision:
A comprehensive tool that enables administrators to identify, monitor, and analyze specific application data flows without using taps to ensure optimized performance.
- Forward Error Correction (FEC):
Enables recovery from bit errors in device connections and ISLs, enhancing transmission reliability and

Standard Features

performance.

HPE SANnav Management Software

HPE SANnav Management Software is the next-generation SAN management application suite for HPE B-series SAN environments. It consists of SANnav Management Portal Software and SANnav Global View Software:

- SANnav Management Portal is a next-generation SAN management application with a simple browser-based user interface (UI) streamlining common workflows, such as configuration, zoning, deployment, troubleshooting, and reporting.
- SANnav Global View helps administrators visualize the health, performance and inventory of multiple SANnav Management Portal instances at data centers across the globe or a single multi-tenant data center using a simple, intelligent dashboard.

SANnav Management Portal and SANnav Global View not only transform SAN telemetry data into useful insights, such as health and performance scores, but also enable administrators to quickly associate real-time data with historical metrics and logs for in-depth analysis. This can help with spotting trends, establishing baselines, and identifying any behavioral changes over time.

HPE SANnav Management Software is available as a term-license for 1-year, 3-years and 5-years period as both - physical and electronic License-to-Use (LTU). It supports 8Gb, 16Gb and 32Gb FC Switches and Directors.

ISL Trunking

For high performance and seamless failover, this optional license logically groups up to eight E_ports (switch mode) or F_ports (Access Gateway mode) to provide a high bandwidth trunk between two HPE B-Series or Brocade switches. Each switch needs its own license. The fabric operating system views the trunk as a single, high bandwidth ISL resource (up to 256 Gbps when routing connections between 32 Gb/s capable switches). Connections are load-balanced across the individual links, which comprise the logical trunk group.

HPE Synergy Frame 12000 compatibility

Brocade 32Gb FC SAN Switch Module for HPE Synergy must be deployed within the HPE's Composable Infrastructure solution, and is compatible only with HPE Synergy Frames.

HPE FC HBA Mezzanines

16Gb and 32Gb HPE Fibre Channel Mezzanine cards for HPE Synergy are supported

- Please refer to the HPE FC Mezzanine HBA Product QuickSpecs for Compute Module support details. Support for the 32Gbps FC HBA Mezzanine with the Brocade 32Gb SAN Switch for HPE Synergy requires HPE FOS v8.2.0_gft or later

HPE Synergy Frame Frame

HPE Synergy Frame 12000

Switch interoperability

HPE B-Series Switches, Directors, and Routers

32Gbps Fibre Channel Switches and Directors

- SN8600B 32Gb Director Switch (Enterprise)
- SN6650B 32Gb Fibre Channel SAN Switch
- SN6600B 32Gb Fibre Channel Switch (Midmarket)
- SN3600B 32Gb Fibre Channel Switch (Entry)
- Brocade 32Gb Gb SAN Switch Module for HPE Synergy

Standard Features

16Gb/s Fibre Channel Switches and Directors

- SN8000B 16Gb Director Switch (Enterprise)
- SN6500B 16Gb Fibre Channel SAN Switch
- SN6000B 16Gb Fibre Channel Switch (Midmarket)
- SN3000B 16G Fibre Channel Switch (Entry)
- Brocade 16 Gb SAN Switch for HPE c-Class BladeSystem
- Brocade 16Gb Fibre Channel SAN Switch Module for HPE Synergy

8 Gb Switches

- 8/24 SAN Switch
- 8/8 SAN Switch
- Brocade 8 Gb SAN Switch for HPE c-Class BladeSystem

Virtual Connect

- HPE Virtual Connect 8Gb 24-port Fibre Channel Module
- HPE Virtual Connect 8Gb 20-port Fibre Channel Module
- HPE Virtual Connect 16 Gb 24-port Fibre Channel Module
- HPE Virtual Connect 32 Gb 24-port Fibre Channel ModuleHPE Virtual Connect FlexFabric 10Gb/24-Port Module for c-Class BladeSystem
- HPE Virtual Connect FlexFabric-20/40 F8 Module for c-class Blade System
- HPE Virtual Connect SE 16Gb Fibre Channel Module for HPE Synergy
- HPE Virtual Connect SE 40GB F8 Module for HPE Synergy

Multi-Protocol Routers and Gateways

- HPE StoreFabric SN8600B 32Gb SAN Extension Blade
- HPE Multi-protocol Extension Blade
- HPE StoreFabric SN4000B FC SAN Extension Switch
- HPE 1606 SAN Extension Switch

Family Comparison			
Features	Brocade 16Gb SAN Switch for HPE c-Class BladeSystem	Brocade 16Gb Fibre Channel SAN Switch Module for HPE Synergy	Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy
Targeted Environment	Enterprise, Datacenters, Workgroups, Departments	Enterprise, Datacenters, Workgroups, Departments	Enterprise, Datacenters, Workgroups, Departments
Port Bandwidth	16Gbps	16Gbps	32Gbps
Aggregate device bandwidth	448 Gbps (28 ports x 16 Gbps)	576 Gbps (36 ports x 16 Gbps)	896 Gbps (28 ports x 32 Gbps)
OS Support	Please Refer to SPOCK https://www.hpe.com/storage/spock		
Storage system Support	3PAR StoreServ, Nimble, StoreVirtual 4000, P9000/XP7, P6000/EVA, P2000/MSA		3PAR StoreServ, Nimble, XP7, MSA 2050/1050
FC Ports	12 external /16 internal	8 SFP+ external, 4 QSFP external /12 internal (24 maximum)	8 SFP+ external, 2 QSFP external /12 internal
SFP	B-series	B-series	B-series

Standard Features

Advanced Trunking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Adaptive Networking	Included	Included	Included
Fabric Vision Software	Included with HPE PowerPack+ upgrade	Included with HPE PowerPack+ upgrade	Included with HPE PowerPack+ upgrade
Form factor	Embedded	Embedded	Embedded
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	Yes, in BladeSystem Enclosure	Yes, in BladeSystem Enclosure	Yes, in Synergy Frame
Hot plug fans	Yes, in BladeSystem Enclosure	Yes, in BladeSystem Enclosure	Yes, in Synergy Frame

Service and Support

Warranty

Hardware Warranty - Three-year on-site warranty, normal business hours, next business day response, and installation not included.

Notes: The hardware warranty covers firmware and embedded non-saleable software. Saleable software carries its own warranty, please see below.

Software Warranty: Hewlett Packard Enterprise warrants only that the software media will be free of physical defects for a period of ninety (90) days from delivery.

Notes: The entire liability of Hewlett Packard Enterprise and its suppliers and your exclusive remedy for software that does not conform to this Limited Warranty shall be the repair or replacement of the defective media. This warranty and remedy are subject to your returning the defective media during the warranty period to Hewlett Packard Enterprise in the country in which you obtained the software.

Services Included with Product Purchase

The Brocade 32Gb/20 Power Pack+ Fibre Channel SAN Switch Module for HPE Synergy (Q2E57A) includes 3-years of Hewlett Packard Enterprise standard business hours, standard business days Software Support (includes software technical support and software product and documentation updates)..

The Brocade 32Gb Fibre Channel SAN Switch Module Power Pack+ LTU for HPE Synergy (Q2E60A, Q2E60AAE) includes 1-year of Hewlett Packard Enterprise standard business hours, standard business days Software Support (includes software technical support and software product and documentation updates).

HPE Pointnext - Service and Support

Get the most from your HPE Products. Get the expertise you need at every step of your IT journey with **HPE Pointnext Services**. We help you lower your risks and overall costs using automation and methodologies that have been tested and refined by HPE experts through thousands of deployments globally. HPE Pointnext **Advisory Services**, focus on your business outcomes and goals, partnering with you to design your transformation and build a roadmap tuned to your unique challenges. Our **Professional** and **Operational Services** can be leveraged to speed up time-to-production, boost performance and accelerate your business. HPE Pointnext specializes in flawless and on-time implementation, on-budget execution, and creative configurations that get the most out of software and hardware alike.

Consume IT on your terms

HPE GreenLake brings the cloud experience directly to your apps and data wherever they are-the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake accelerates digital transformation in a distributed, edge-to-cloud world.

- Get Faster time to market.
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

Managed services to run your IT operations

HPE GreenLake Management Services provides services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

Service and Support

Free up resources with Operational Services from HPE Pointnext

HPE delivers services for IT by using proven best practices as well as automation and methodologies that have been tested and refined by HPE experts and artificial intelligence through thousands of deployments globally. Choose from the recommended services for customers purchasing from Hewlett Packard Enterprise or an authorized reseller. Services are quoted using Hewlett Packard Enterprise order configuration tools.

Recommended Services

HPE Pointnext Tech Care.

HPE Pointnext Tech Care is the new operational service experience for HPE products. Tech Care goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Pointnext Tech Care has been reimaged from the ground up to support a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Pointnext Tech Care is available in three response levels. Basic, which provides 9x5 business hour availability and a 2 hour response time. Essential which provides a 15 minute response time 24x7 for most enterprise level customers, and Critical which includes a 6 hour repair commitment where available and outage management response for severity 1 incidents.

<https://www.hpe.com/services/techcare>

HPE Pointnext Complete Care

HPE Pointnext Complete Care is a modular, edge-to-cloud IT environment service that provides a holistic approach to optimizing your entire IT environment and achieving agreed upon IT outcomes and business goals through a personalized and customer-centric experience. All delivered by an assigned team of HPE Pointnext Services experts. HPE Pointnext Complete Care provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

<https://www.hpe.com/services/complecare>

HPE Education Services

Provides comprehensive training designed to expand the skills of your IT staff and keep them up to speed with the latest technologies.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options

HPE Support Center

The HPE Support Center is a personalized online support portal with access to information, tools and experts to support HPE business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers.

Learn more <http://www.hpe.com/support/hpesc>

Hewlett Packard Enterprise Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a HPE warranty, HPE Support Service or HPE contractual support agreement.

Notes : *HPE Support Center Mobile App is subject to local availability.

Service and Support

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Defective Media Retention

An option available with HPE Pointnext Complete Care and HPE Pointnext Tech Care and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

For more information

- <http://www.hpe.com/services>
- <https://www.hpe.com/us/en/services/operational.html>

To learn more on HPE Storage Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "**Contact HPE**

<https://www.hpe.com/us/en/contact-hpe.html>

HPE Support Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
 - Customers purchasing from a commercial reseller can find HPE Support Services at <https://ssc.hpe.com/portal/site/ssc/>
-

Configuration Information

Step 1 - Base Configurations (Select one.)

Description	SKU
Brocade 32Gb/12 2SFP+ Fibre Channel SAN Switch Module for HPE Synergy <ul style="list-style-type: none">(1) 32Gbps SAN Switch12 ports enabled for any combination (12 internal and 16 external)2 32Gb SFP+ includedDual function mode - Native OS (default) or Access Gateway ModeDocumentation	Q2E55A
Brocade 32Gb/20 4SFP+ Fibre Channel SAN Switch Module for HPE Synergy <ul style="list-style-type: none">(1) 32Gbps SAN Switch20 ports enabled for any combination (12 internal and 16 external)4 32Gb SFP+Dual function mode - Native OS (default) or Access Gateway ModeDocumentation	Q2E56A
Brocade 32Gb/20 4SFP+ Power Pack+ Fibre Channel SAN Switch Module for HPE Synergy <ul style="list-style-type: none">(1) 32Gbps SAN Switch20 ports enabled for any combination (12 internal and 16 external)4 32b SFP+Dual function mode - Native OS (default) or Access Gateway ModeDocumentation and includes Power Pack+ Bundle and management tools (see software components, optional)	Q2E57A

Step 2 - Additional Options

Select each type of required options with quantities specified.

Hardware

32Gbps QSFP / 32Gbps Optical Transceivers (SFP28)

HPE B-series 4x32Gb 1-pack Short Wave QSFP Transceiver	Q2R27A
HPE B-series 4x32Gb 1-pack Long Wave 2km QSFP Transceiver	Q2R31A
HPE B-series 4x32Gb QSFP28 Short Wave 100m 1-pack Secure Transceiver	R6B20A

Notes: QSFPs (4 lanes of 32Gb) support MPO/MPO Multi-mode as well as 4/LC breakout cables

HPE B-series 32Gb SFP28 Short Wave 8-pack Secure Transceiver	R6W26A
HPE B-series 32Gb SFP28 Long Wave 10km 1-pack Secure Transceiver	R6B13A

16Gb/s QSFP 16Gb/s Optical Transceivers (SFP+)

HPE B-series 4x16 Short Wave QSFP Transceiver	K2Q87A
HPE B-series 16Gb SFP+ Short Wave Transceiver	QK724A
HPE B-series 16Gb SFP+ Short Wave 8-pack Secure Transceiver	R6W28A
HPE B-series 16Gb SFP+ Long Wave 10km 1-pack Secure Transceiver	R6B11A

Optical cables

PremierFlex OM4 LC/LC Multi-mode Cables

HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable	QK737A

Configuration Information

Description	SKU
OM3 LC/LC Multi-mode Cables	
HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
QSFP to 4xLC Breakout Cables	
HPE Multi Fiber Push On to 4 x Lucent Connector 5m Cable	K2Q46A
HPE Multi Fiber Push On to 4 x Lucent Connector 15m Cable	K2Q47A
HPE Premier Flex MPO to 4xLC 30m Cbl	Q1H68A
HPE Premier Flex MPO to 4 x Lucent Connector 50m Cable	Q1H69A
OM4 MPO/MPO Multi-mode Cables	
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 1m Cable	Q1H63A
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 2m Cable	Q1H64A
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 5m Cable	Q1H65A
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 10m Cable	QK729A
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 15m Cable	Q1H66A
HPE Premier Flex MPO/MPO Multi-mode OM4 12 Fiber 30m Cable	Q1H67A
HPE Premier Flex MPO/MPO Multi-mode OM4 8 Fiber 50m Cable	QK731A
HPE Premier Flex MPO/MPO OM4 100m Cable	H6Z30A
Software	
Power Pack+ Software Bundle	
Brocade 32Gb Fibre Channel SAN Switch Module Power Pack+ E-LTU for HPE Synergy	Q2E60AAE
Notes: Physical License - Q2E60A	
(For upgrading Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy to Power Pack+). Includes bundled license for:	
<ul style="list-style-type: none">• Fabric Vision (Includes IO Insight and VM Insight Software)• ISL Trunking• Extended Fabrics	
Brocade 32Gb Fibre Channel SAN Switch Module 8-port Upgrade E-LTU for HPE Synergy	Q2E58AAE
Notes: Physical License - Q2E58A	
Notes:	
–The Brocade 32Gb FC Switch Module for HPE Synergy is capable of supporting 40 FC ports, up to 16 uplink FC ports and up to 24 downlink FC ports. However with Dual Port 32Gb FC Mezzanine cards, only a maximum of 12 downlinks are supported. This allows each Brocade 32Gb Fibre Channel SAN Switch Module for HPE Synergy to support a maximum of 28 FC ports. The Brocade 32Gb Fibre Channel SAN Switch Module 8-port Upgrade LTU provides up to 8 additional usable ports. This LTU adds ports in increments of 8 up to a current total of 28 usable ports.	
–For example, for the 32Gb/12 port base model you can add up to (QTY) 2 8-port upgrade LTUs or for the 32Gb/20-port models you can add (QTY) 1 8-port upgrade LTU totaling 28 ports.	
–In order to obtain Extended Fabrics Software or ISL Trunking Software or Fabric Vision Software, a purchase of the Q2E60AAE Power Pack+ Software Bundle is required.	

Configuration Information

Description	SKU
HPE SANnav Management Portal Base 1yr E-LTU	R3P45AAE
Notes: Physical License - R3P45A	
HPE SANnav Management Portal Enterprise 1yr E-LTU	R3P46AAE
Notes: Physical License - R3P46A	
HPE SANnav Global View 1yr E-LTU	R3P47AAE
Notes: Physical License - R3P47A	
HPE SANnav Management Portal Base 3yr E-LTU	R3P48AAE
Notes: Physical License - R3P48A	
HPE SANnav Management Portal Enterprise 3yr E-LTU	R3P49AAE
Notes: Physical License - R3P49A	
HPE SANnav Global View 3yr E-LTU	R3P50AAE
Notes: Physical License - R3P50A	
HPE SANnav Management Portal Base 5yr E-LTU	R4P29AAE
Notes: Physical License - R4P29A	
HPE SANnav Management Portal Enterprise 5yr E-LTU	R4P30AAE
Notes: Physical License - R4P30A	
HPE SANnav Global View 5yr E-LTU	R4P31AAE
Notes: Physical License - R4P31A	

- Notes:
- The Base edition of HPE SANnav Management Portal does not support management of director class switches.
 - While installing HPE SANnav Management software, there is an option to install a 90-day full-featured free trial version of the SANnav Management Portal and SANnav Global View version. The trial version includes full functionality but expires after the trial period.
 - HPE SANnav Management Software License-to-Use (LTU/E-LTU) includes maintenance and support for the duration of the license. At the end of the license period, customer needs to purchase a new license to continue using the software. Software renewal via HPE PointNext is not allowed/supported.

Technical Specifications

Fibre Channel ports

12 Internal 16/32Gbps (downlink) ports; up to 16 External 8/16/32 Gbps auto-sensing (8x SFP+ and 2x QSFP+) (uplink) - universal (E, F, N, D) ports. For the 32Gb/20 Port SAN Switch model: up to 20 ports in any internal/external port combination enabled. Depending on SAN switch model selected, order the total number of Brocade 32Gb Fibre Channel SAN Switch Module 8-port Upgrade E-LTU or LTU for HPE Synergy to increase active FC port counts.

Device support and Scalability guidelines

https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-c04787660

Performance

32Gbps line speed, full duplex

Certified maximum

Certified maximum information available at

https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-c04787660

Switch core

Non-blocking

Fabric latency

<=900 nanoseconds through the use of cut-through frame routing at 32Gbps (includes FEC logic delay)

Maximum frame size

2112-byte payload

Classes of service

Class 2, Class 3, Class F (inter-switch frames)

Port types

D_Port (Diagnostic port), E_Port, F_Port; optional port type control Brocade Access Gateway mode: F_Port and NPIV-enabled N_Port

Data traffic types

Fabric switches supporting unicast

Media types

Hot-pluggable, B-Series Branded Small Form Factor Pluggable (SFP), LC connector; Short-Wave Laser (SWL), Long-Wave Laser (LWL); Extended Long-Wave Laser (ELWL); distance depends on fiber-optic cable and port speed. Supports QSFP+ (32/16/8 Gbps) and/or SFP+ (32/16/8 Gbps) optical transceivers.

Advanced

Short-wave, long-wave, and extended long wave laser transceivers are supported

Technical Specifications

Fabric services

Simple Name Server, Registered State Change Notification (RSCN). Includes Advanced WebTools and Advanced Zoning. Optional advanced fabric services include: Fabric Vision, ISL Trunking, and Extended Fabrics.

Options

SFP media, port upgradeable licensing, advanced management software licensing

Supported software

Telnet, SSH, SNMP (FE MIB, FC Management MIB), HPE Storage Operations Manager, Advanced WebTools, Advanced Zoning, HPE SANnav Management Software, SmartSAN, StoreFabric Orchestrator and Anisible Automation

Management access

Web Tools, SMI-s provider, REST API, SNMP, Telnet, and SSH

Diagnostics

Cable diagnostic (D_Port), including electrical/optical loopback, link traffic/latency/distance

Power consumption

Typical 50W, maximum is 70W (with all ports running at maximum speed)

Dimensions	Depth	1.08 in. (2.75 cm.)	
	Height	11.05 in. (28.07 cm.)	
	Width	16.92 in. (42.97 cm.)	
	Weight	Approx. 7.0 lb. (3.18 kg.) - without media	
Environment	System Inlet Temperature	Operating	Inlet air temperature up to 43°C (109.4°F) at sea level with an altitude derating of 1.0°C per every 1000 feet of elevation above sea level to a maximum operating altitude. For example, the maximum inlet air-temperature requirement at 5000 ft. above sea level is 38°C.
		Non-operating	-40°C to 70°C (-40° to 158°F). Maximum rate of change is 20°C/Hr (36°F/Hr).
	Relative Humidity	Operating	5 to 95% relative humidity, 38.7°C maximum wet bulb temperature, and Non-condensing.
		Non-operating	5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.
	Altitude	Operating	3050 m (10,000 ft.). This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
		Non-operating	9144 m (30,000 ft.). Maximum allowable altitude change rate is 457 m/min (1500 ft. /min).
Vibration	Operating	1 G, 10-500 Hz, 60 minutes per axis	
	Non-operating	2 G, 10-500 Hz, 30 minutes	

Technical Specifications

Shock	Operating	Half-sine-wave shock, 40 G, 2 ms duration, in each direction of three mutually perpendicular axes.
	Non-operating	Half-sine-wave shock, 140 G, 2 ms duration, in each direction of three mutually perpendicular axes; and square-wave shock up to 80 G, 180 inches/s velocity change, in each direction of three mutually perpendicular axes.

Summary of Changes

Date	Version History	Action	Description of Change
04-Oct-2021	Version 7	Changed	Service and Support section was updated Obso SKU was removed
02-Aug-2021	Version 6	Changed	Service and Support, and Configuration Information sections were updated.
07-June-2021	Version 5	Changed	Added 16Gb and 32GB SW and LW transceivers
10-Aug-2020	Version 4	Changed	Overview, Standard Features and Configuration Information sections were updated.
03-Feb-2020	Version 3	Changed	Standard Features, Service and Support, and Configuration Information sections were updated.
07-Oct-2019	Version 2	Changed	Overview, Standard Features, Service and Support, Configuration Information, and Technical Specifications sections were updated.
02-Apr-2019	Version 1	New	New QuickSpecs

Copyright

Make the right purchase decision. Contact our presales specialists.



Chat



Email



Call



Get updates



Hewlett Packard
Enterprise

© Copyright 2021 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a00062177enw - 16377 - Worldwide - V7 - 04-October-2021