## Key **Features**

- Ergonomic flexibility with quick-release stand
- vDisplay Manager productivity software for maximised multitasking
- Dual front facing speakers for clear audio
- HDMI, DisplayPort, VGA, and USB3.2 ports for extended connectivity
- 3-Sided narrow bezel for uninterrupted viewing



## Product **Description**

The ViewSonic VG2440 is a 24" Full HD ergonomic business monitor designed to increase productivity and efficiency within the home and office workspace. Providing the full spectrum of ergonomic flexibility, the VG2440 can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow, while the built-in vDisplay Manager productivity software delivers efficient multi-tasking ability and streamlined display control. Dual front-facing speakers ensure a perfect audio-visual experience to provide teams with quality remote communication and collaboration. The beautifully designed display includes a 3-sided narrow bezel for uninterrupted viewing in multi-monitor display setups as well HDMI. DisplayPort, VGA, and USB3.2 connectivity. Complete with an easy-to-install quick release stand that reduces setup time to only a few minutes, the VG2440 offers a high-performance, purpose-built display solution designed for workspace productivity.



- Menu Control Panel
  VESA Compatible(Wall Mount 100 x 100mm)

- 3. AC In 4. Line-in 5. Headphone 6. Display Port1.2

- 7. HDMI 8. D-Sub 9. USB 3.0 Up Stream(Type B)
- 10. USB 3.0 Down Stream(Type A) 11. USB 3.0 Down Stream(Type A)

DISPLAY		INPUT SIGNAL	
Display Size (in.):	24		RGB Analog: 16 ~ 83KHz, HDMI
Viewable Area (in.):	23.6	Frequency Horizontal:	(v1.4): 15 ~ 90KHz, DisplayPort (v1.2): 15 ~ 90KHz
Panel Type:	VA Technology	- W.C.	RGB Analog: 50 ~ 75Hz, HDMI
Resolution:	1920 x 1080	Frequency Vertical:	(v1.4): 49 ~ 75Hz, DisplayPort (v1.2): 49 ~ 75Hz
Resolution Type:	FHD	VIDEO INPUT	
Static Contrast Ratio:	3,000:1 (typ)	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Dynamic Contrast Ratio:	80M:1		Separate/Composite/SOG - RGB
Light Source:	LED	Analog Sync:	Analog
Brightness:	250 cd/m² (typ)	ERGONOMICS	
Colours:	16.7M	Height Adjust (mm):	130
Colour Space Support:	8 bit (6 bit + Hi-FRC)	Swivel:	120°
Aspect Ratio:	16:9	Tilt (Forward/Back):	-5° / 40°
Response Time (Typical GTG):	5ms	Pivot (Right/Left):	90° / 90°
Response Time (GTG w/OD):	5ms	WEIGHT (IMPERIAL)	
Viewing Angles:	178º horizontal, 178º vertical	Net (lbs):	12.9
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (lbs):	7.5
Curvature:	Flat	Gross (lbs):	18.7
Refresh Rate (Hz):	60	WEIGHT (METRIC)	
Blue Light Filter:	Yes	Net (kg):	5.8
Flicker-Free:	Yes	Net Without Stand (kg):	3.4
Colour Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Gross (kg):	8.5
Pixel Size:		DIMENSIONS (IMPERIAL) (W	·
Surface Treatment:	0.272 mm (H) x 0.272 mm (V)	Packaging (in.):	24 x 15.9 x 8.3
COMPATIBILITY	Anti-Glare, Hard Coating (3H)	Physical (in.):	21.6 x 15.12~20.22 x 8.1
PC Resolution (max):	1920x1080	Physical Without Stand (in.):	21.6 x 12.9 x 2
Mac® Resolution (max):	1920x1080	DIMENSIONS (METRIC) (WX	
. ,	Windows 7/8/8.1/10 certified; macOS	Packaging (mm):	609 x 405 x 210
PC Operating System:	tested	Physical (mm):	549 x 384.07~513.58 x 206
Mac® Resolution (min):	1920x1080	Physical Without Stand (mm):	549 x 329 x 50
CONNECTOR		GENERAL	aTIMus FCC B ICESONS Energy
VGA:	1	Regulations:	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX- CoC, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, TCO
USB 3.2 Type A Down Stream:	4		
USB 3.2 Type B Up Stream:	1		8.0, EAC, UkrSEPRO, UKCA
3.5mm Audio In:	1	PACKAGE CONTENTS:	VG2440 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Audio Cable (Male-
3.5mm Audio Out:	1		
HDMI 1.4:	1		Male) x1, Quick Start Guide x1
DisplayPort:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Power in:	3-pin Socket (IEC C14 / CEE22)	Warranty:	*Warranty offered may differ from
AUDIO		warranty.	market to market
Internal Speakers:	2Watts x2	Power Management:	Energy Star standards, EPEAT
POWER			
Eco Mode (Conserve):	11.81W		
Eco Mode (optimised):	13.08W		
Consumption (typical):	14.85W		
Consumption (max):	16.24W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organisation:	Yes		
CONTROLS	W 4/ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		