


















B360 PRO FULLY RUGGED LAPTOP

- MIL-STD 810H, 6ft operating drop rating, IP66 certified, and optional salt fog resistant
- 12th Generation Intel® Core™ Processor
- 13.3" FHD LumiBond® display with Getac sunlight readable technology (1,400 nits) and capacitive touchscreen
- Optional NVIDIA® GeForce® GTX1650 4GB discrete graphics controller
- Enhanced enterprise security with optional dual user replaceable storage, Windows Hello face-authentication camera, integrated 1D/2D imager barcode reader and multi-factor authentication options
- LifeSupport™ battery swappable technology



SPECIFICATIONS

Generation

Operating System Windows 11 Pro

Mobile Computing Platform

Intel® Core™ i5-1240P Processor Max. 4.4GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-1250P vPro® Processor
Max. 4.4GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Intel[®] Core™ i7-1260P Processor Max. 4.7GHz with Intel® Turbo Boost Technology
- 18MB Intel® Smart Cache

Intel® Core™ i7-1270P vPro® Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 18MB Intel® Smart Cache

Intel® Core™ i7-1280P vPro® Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 24MB Intel® Smart Cache

VGA Controller

Intel® Iris® Xe Graphics | Optional: NVIDIA® GeForce® GTX1650 4GB discrete graphics controller

Display
13.3" Wide Viewing Angle TFT LCD FHD (1920 x 1080)
Protection film
100 - its LumiBond® display with Getac sunlight read 1,400 nits LumiBond® display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory
8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD
Optional: 512GB / 1TB / 2TB PCIe NVMe SSD
Optional 2nd storage ^N: 256GB / 512GB / 1TB / 2TB PCIe

Optional multimedia bay storage : 1TB / 2TB SATA SSD

Keyboard LED backlit membrane keyboard

Pointing Device

Capacitive multi-touch screen

Touchpad - Touchpad with two buttons

Smart card reader x 1
Optional: SD card reader x 1
Optional: Discrete graphics controller, or PCMCIA Type II,
or ExpressCard/54 TOPTION OF THE PROPRESS OF T

Multimedia Bay

Configurable options vvi : 1. Optional: DVD super multi drive, or Blu-Ray super multi drive, or 3rd storage

2. Optional: 3rd battery

I/O Interface

5M webcam x 1 xxii Audio in/out combo x 1 Audio In/out combo x i DC in Jack x 1 Powershare USB 3.2 x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt™ 4 Type-C x 1 vii LAN (RJ45) x 1 HDMI 2.0 x 1

Docking connector x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) viii Optional: Windows Hello face-authentication FHD camera

(front-facing) x 1 xxii Optional: RF antenna pass-through for GPS, WWAN and

1. Serial port (9-pin; D-sub) x 1 + External VGA (13-pin; D-sub) x 1 2. Serial port (9-pin; D-sub) x 1 + Display port x 1 3. Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1 + 2nd LAN (RJ45) x 1

4. Serial port (9-pin; D-sub) x 1 + Display port x 1 + 2nd LAN (RJ45) x 1 Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-

5. Serial port (9-pin; D-sub) x 2 + External vGA (15-pin; D-sub) x 1 6. Serial port (9-pin; D-sub) x 2 + Display port x 1 7. Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-sub) x 1 + 2nd LAN (RJ45) x 1 8. Serial port (9-pin; D-sub) x 2 + Display port x 1 + 2nd LAN

Communication Interface

10 / 100 / 1000 base-T Ethernet Intel[®] Wi-Fi 6E AX211, 802.11ax

Bluetooth (v5.3) X
Optional: Dedicated GPS with L1/L5 XXIIII

Optional: 4G LTE mobile broadband with integrated GPS viii,

Optional: 5G Sub-6 with integrated L1/L5 GPS xxiii, xxiv

Security Features

TPM 2.0 Kensington lock Smart card reader

Optional: Fingerprint reader ^{xi} Optional: HF RFID reader ^{xi, xii} Optional: Windows Hello face-authentication FHD camera

(front-facing) [»]

AC adapter (90W, 100-240VAC, 50/60Hz)
AC adapter (120W, 100-240VAC, 50/60Hz)
High capacity Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh) x 2
Optional: Multimedia bay battery (11.1V, typical 4200mAh;

min. 2080mAh) x 1
LifeSupport™ battery swappable technology

Dimension (W x D x H) & Weight 342 x 281 x 53.5mm (13.46" x 11.06" x 2.11") 3.08Kg (6.79lbs) ^{xiii}

Rugged Feature MIL-STD-810H certified IP66 certified MIL-STD-461G certified xiv Vibration & 6ft (1.8m) drop resistant Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) Optional: Salt fog certified

Environmental Specification

Temperature $^{\rm xvi}$: - Operating: -29°C to 63°C / -20°F to 145°F $^{\rm xvii}$ - Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH, non-condensing

Pre-installed software

Getac Utility Getac Geolocation

Getac Barcode Manager xviii Optional: Absolute Persistence

Optional software

Getac Driving Safety Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility xix

Office Dock

Serial Port	1	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	6	5
LAN	2	2
HDMI 1.3	1	1
RF Antenna Connector	3 (GPS, WWAN, WLAN)	-

Vehicle Dock

B360 PRO FULLY RUGGED LAPTOP

High capacity Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh) AC adapter (90W, 100-240VAC) Capacitive stylus with tether

Optional:

Carry bag High Capacity Li-ion Battery (10.8V, typical 6900mAh; min. 6600mAh) 6600mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (90W, 100-240VAC)
AC adapter (120W, 100-240VAC)
MIL-STD-461 AC adapter (90W, 100-240VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Capacitive stylus with tether
Protection film
Vehicle cradle **

Vehicle cradle Vehicle dock ** Office dock Spare SSD kit 100W Type-C adapter xxi

Bumper-to-Bumper warranty

Bumper-to-Bumper warranty
Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.
That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.
Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

years Bumper-to-Bumper

Units equipped with dual channel memory come with Intel®

III.

IV.

Units equipped with dual channel memory come was meel riss "X Graphics.

120W AC adapter is used for office dock and for device configured with discrete graphics card.

Discrete graphics card, PCMCIA slot, and Expresscard slot are mutually exclusive.

Second storage is optional and will be fitted with a removable cover when not chosen at point of purchase.

Option 1 and 2 are mutually exclusive.

Factory option. Not user swappable.

The configuration with a discrete graphic controller does not support USB-C power delivery function.

Units with 4G LTE option come with an embedded SIM card slot.

\/III

Units With 46 LTE Option come with an embedded since a slot. External VGA and Display port are mutually exclusive. External VGA and Display port are mutually exclusive. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Fingerprint reader and HF RFID reader are mutually exclusive. HF(1.3.56MHz) combo HF RFID/NFC reader (Class, HID Prox, ISO 15693, 14443 A/B, Miffare and FelicaTM compliant). Weight and dimensions vary from configurations and oottonal accessories.

XIII.

weight and dimensions vary from configurations and optional accessories.
MIL-5TD-461 90W AC adapter sold separately.
Available with limited configurations and environment conditions.
Tested by an independent third-party test lab following MIL-STD-810H.

X\/II

For the control of th XVIII. XIX. XX. XXI. XXII.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel: +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I

www.getac.com/en/Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.