

# Product datasheet

Specifications



APC Smart-UPS On-Line,  
2200VA, Rackmount 2U, 230V, 8x  
C13+2x C19 IEC outlets, Network  
Card, Extended runtime, W/ rail kit

SRT2200RMXLI-NC

## Overview


Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	

## Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	2U
Cable length	2.4 m
Number of cables	1
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Network management card Rack mounting hardware Rack mounting brackets Rack mounting support rails USB cable Warranty card
Range of product	Smart-UPS On-Line

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery type	Lead-acid battery
Battery voltage	72 V

Extended runtime	1
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC141</a> 
Battery charger power	122 W rated

## General

Number of power module	1400
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
UPS type	Double conversion online

## Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	58.4 cm
Net weight	25 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

## Input

Input voltage limits	100...275 V adjustable (half load)
Network frequency	40...70 Hz auto-sensing

## Output

Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Wave type	Sine wave

---

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

## Conformance

---

Product certifications	CE EAC RCM VDE UK PSTI
------------------------	------------------------------------

---

Marking	CE Mark
---------	---------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

## Environmental

---

Acoustic level	55 dBA
----------------	--------

---

Heat dissipation	535 Btu/h
------------------	-----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Ambient air temperature for storage	-20...50 °C
-------------------------------------	-------------

---

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

---

IP degree of protection	IP20
-------------------------	------

---

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

## Communications & Management

---

Emergency power off	Yes
---------------------	-----

---

Free slots	1
------------	---

---

Preinstalled device	Network management card 3 with environmental monitoring
---------------------	---

---

Alarm	Audible and visible alarms : prioritized by severity
-------	--

## Surge Protection and Filtering

---

Surge energy rate	340 J
-------------------	-------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	24.500 cm
------------------	-----------

---

Package 1 Width	60.000 cm
-----------------	-----------

---

Package 1 Length	81.500 cm
------------------	-----------

---

Package 1 Weight	33.105 kg
------------------	-----------

---

Unit Type of Package 2	P12
------------------------	-----

---

Number of Units in Package 2	3
------------------------------	---

---

Package 2 Height	90.000 cm
------------------	-----------

---

Package 2 Width	80.000 cm
-----------------	-----------

---

Package 2 Length	120.000 cm
------------------	------------

---

Package 2 Weight 111.315 kg

## Logistical informations

---

Country of origin PH

## Contractual warranty

---

Warranty 3 years repair or replace (excluding battery) and 2 years for battery

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 3657

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 4282bd22-a353-4f82-bb5c-97bbd7f1d1e9

REACH Regulation [REACH Declaration](#)

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery User replaceable

Take-back Yes