FUJITSU

Data Sheet FUJITSU PRAID EP400i / EP420i

RAID Controller SAS 12Gbit/s 1GB or 2GB cache based on LSI MegaRAID® for internal storage devices

The RAID concept (Redundant Array of Independent Disks) refers to several independent hard disks which form a large logical drive when switched together.

Redundancy information is calculated from several data blocks (except for RAID 0) and saved distributed to the individual hard disks. Your operating system no longer accesses the individual hard disks, but the array.

The actual objective of the RAID concept is to increase availability and prevent downtimes in the event of a hard disk failure. However, the theoretical security of the RAID concept is only as good as the RAID controller used. Benefit from the Fujitsu RAID controllers where technology, experience and practical implementation all ensure the security that your company needs in the event of an emergency.

PRAID EP400i / EP420i

The Fujitsu RAID ControllerPRAID EP400i with 8 ports sets new speed and data security standards for internal storage drives. The RAID stack is based on the LSI MegaRAID® and offers high data throughput, a comprehensive fault tolerance function and user-friendly management options. Moreover, the Controller management is integrated seamlessly into the Fujitsu server management concept. All controller functions are supported by the Fujitsu ServerView RAID Manager. The PRAID EP400i is designed for backward compatibility with 3Gbit/s SAS as well as with 6Gbit/s and 3Gbit/s SATA hard

drives. Regardless of the drive speed, it delivers significant performance improvements in both read and write applications. Due to the support of 64-bit addressing, a robust set of RAID features and demanding error tolerance functions the controller provides high RAID performance and data availability. Powerful online management service programs (Fujitsu ServerView RAID Manager), which are simple to operate and quick to install, provide the administrator with unparalleled flexibility and access to the arrays. The RAID controller supports all of the important RAID levels including RAID 6 and 60. The optional flash battery backup (FBU) combined with TFM module ensures the integrity of the data stored in the cache on the RAID controller in case of a power outage. In this event, the data will be copied to a non-volatile flash memory (TFM). The FBU provides a low-priced alternative to an uninterruptible power supply (UPS) and, when compared to battery backup up units (BBU), enables a long-term, secure store of data and better serviceability. Always select FBU and TFM module in combination. The Advanced Software Options in combination with Solid State Disks in front of HDD volumes can create high-capacity, high-performance controller cache pools, depending on the load profile. A free of charge test version is available at PRIMERGY-PM. Link: http://docs.ts.fujitsu.com/ dl.aspx?id=c816a64f-8b6d-47df-ba31-836874f08c07



Main Features

- 12Gbit/s SAS ports PCI Express[®] 3.0 x8
- LSISAS3108 12Gbit/s RAID-on-Chip
- 1GB / 2GB 1333MHz DDRIII cache memory
- Optional Flash Backup Unit (FBU)
- Optional SafeStore for PRAID EP420i
- User Management Options
- RAID Advanced Software Options LSI CacheCade[®]. Fast Path is supported free of charge by controller firmware.

Benefits

- Connect up to 240 HDDs and SSDs
- RAID levels 0, 1, 5 and 6 for more data security
- RAID spans 10, 50 and 60 for more data security
- Ensures the integrity in case of power outage, Long-term, secure store of data and better serviceability compared to BBU
- Safe data encryption and data safety for harddisks in case of removal
- Seamless merging of the RAID management into system management
- Create high performance controller cache pools.

Technical details

Technical details

Controller Silicon	B 6 (B 1) B				
	Roc (RAID	on Chip) LSI SAS3108			
Controller type RAID 5/6 Ctrl.		Ctrl.			
		to released operating systems can be found in the server datasheets. Details can be found in the ers list on the support portal.			
Released drivers list link	http://sup	port.ts.fujitsu.com/Download/Index.asp)		
Number of ports	16 ports ir	16 ports int.			
	8 ports int	8 ports int.			
Connector internal	4x SFF864	4x SFF8643 (Mini-SAS HD)			
	2x SFF864	2x SFF8643 (Mini-SAS HD)			
Data transfer rate up to	12 Gbit/s	12 Gbit/s			
Bus type	PCIe 3.0				
Bus width	×8				
RAID Management	StorCLI (co	ServerView RAID Manager StorCLI (command-line interface) BIOS Configuration Utility			
	- Online Ca - Online R - Auto rest - Fast initia - Single co - Load Bal - Configura - Fast initia - Check co - Patrol rea - Up to 64 - S.M.A.R. - Global an - Automa	able stripe size up to 1MB alisation for quick array setup insistency for background data integrity ad for media scanning and repairing logical drives per controller T support nd dedicated Hot Spare with Revertible atic rebuild ure affinity	y - Make Data Consistent (MDC)		
	- Enclosur - SES (in - SGPIO (band) (outband)			
	- Enclosur - SES (in - SGPIO (0, 1, 10, 5	band) (outband) 5, 50, 6, 60			
RAID cache backup unit	- Enclosur - SES (in - SGPIO 0, 1, 10, 5 Optional F	band) (outband) 5, 50, 6, 60 FBU			
RAID level RAID cache backup unit RAID controller notes	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108			
RAID cache backup unit RAID controller notes	- Enclosur - SES (in - SGPIO 0, 1, 10, 5 Optional F based on SAS/SATA/	band) (outband) 5, 50, 6, 60 FBU			
RAID cache backup unit RAID controller notes	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108			
RAID cache backup unit RAID controller notes Interface technology	- Enclosur - SES (in - SGPIO 0, 1, 10, 5 Optional F based on SAS/SATA/	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108	RAID controller cache size	Number of Connectors	
RAID cache backup unit RAID controller notes Interface technology Order code	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on SAS/SATA/ SAS/SATA	iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108 PCIe-NVMe Height of bracket Matching to system	RAID controller cache size 1 GB	Number of Connectors 2	
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E1	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on SAS/SATA/ SAS/SATA	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108 PCIe-NVMe Height of bracket			
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E1 S26361-F5243-E2 S26361-F5243-L1	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on SAS/SATA/ SAS/SATA Product Name PRAID EP400i	iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108 PCIe-NVMe Height of bracket Matching to system	1 GB	2	
RAID cache backup unit	- Enclosur - SES (in - SGPIO (0, 1, 10, 5 Optional F based on SAS/SATA/ SAS/SATA Product Name PRAID EP400i PRAID EP420i	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108 PCIe-NVMe Height of bracket Matching to system Matching to system	1 GB 2 GB	2 2	
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E1 S26361-F5243-E2 S26361-F5243-L1	- Enclosure - SES (in - SGPIO (0, 1, 10, 5 Optional F based on SAS/SATA/ SAS/SATA/ SAS/SATA Product Name PRAID EP400i PRAID EP400i PRAID EP400i	Iband) (outband) 5, 50, 6, 60 FBU LSI SAS3108 PCIe-NVMe Height of bracket Matching to system Matching to system Full Height / Low Profile	1 GB 2 GB 1 GB	2 2 2	

Order code	Product Name	Notes
S26361-F5243-E200	TFM PRAID EP420i/e	installed - Transportable Flash Module - contains flash memory and control logic for Flash Backup Unit (FBU) – required for FBU option
S26361-F5243-E125	RAID Ctrl FBU option for PRAID EP4xx with 25cm cable	installed - Super-capacitor incl. cable
S26361-F5243-E155	RAID Ctrl FBU option for PRAID EP4xx with 55cm cable	installed - Super-capacitor incl. cable
S26361-F5243-E170	RAID Ctrl FBU option for PRAID EP4xxwith 70cm cable	installed - Super-capacitor incl. cable
S26361-F5243-L110	RAID Ctrl FBU option for PRAID EP4xx with 25cm, 55cm, 70cm cable	installed - Super-capacitor incl. cable
S26361-F5243-L660	RAID Advanced Software Options: LSI CacheCade [®] , Fastpath [®]	option / loose delivery - LSI CacheCade® and Fast Path for modular RAID controller and Mezzanine card with 1GB / 2GB cache Testkey available: PRIMERGY-PM
Compliance		
Compliance notes	According to the corresponding system	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PRAID EP400i / EP420i, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PRAID EP400i / EP420i, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://www.fujitsu. com/fts/resources/navigation/terms-of-use. html

Copyright 2018 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html Copyright 2018 FUJITSU LIMITED

Contact Fujitsu Limited Website: www.fujitsu.com/primergy 2018-06-01 WW-EN