

APC NetShelter Rack PDU Advanced Gen 2, Switched Metered Outlet, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 530P6, 48 Outlet

APDU11350SM

Overview

Lead time

Main

Colour	Black	
Product or component type	PDU	
PDU type	Switched metered outlet	
Cord length	3 m	

Complementary

Input Voltage	415 V 3 phases 400 V 3 phases	
Height	1780 mm	
Width	56 mm	
Output Voltage	240 V	
Depth	75 mm	
Net weight	9.6 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 30 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	ou	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	24 A	
Permissible voltage	200240 V 346415 V	
Input current limits	30 A	
Load capacity	17300 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	24 C13/C15/C19/C21 24C13/C15	

Environment

Product certifications	UKCA	
Standards	UL 62368-1	
	CSA C22.2 No 62368-1	
	FCC part 15 Subpart B	
	CE	
	EN 62368-1	
IP degree of protection	IP44	
Ambient air temperature for operation	-560 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	015240 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	198 cm
Package 1 Width	13.2 cm
Package 1 Length	26.2 cm
Package 1 Weight	12.6 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Image of product / Alternate images

Alternative







